



UNIVERSITÀ
DEGLI STUDI
FIRENZE

FLORE

Repository istituzionale dell'Università degli Studi di Firenze

Slope instability mapping around L'Aquila (Abruzzo, Italy) with Persistent Scatterers Interferometry from ERS, ENVISAT and

Questa è la Versione finale referata (Post print/Accepted manuscript) della seguente pubblicazione:

Original Citation:

Slope instability mapping around L'Aquila (Abruzzo, Italy) with Persistent Scatterers Interferometry from ERS, ENVISAT and RADARSAT datasets / Righini G.; Del Conte S.; Cigna F.; Casagli N.. - In: GEOPHYSICAL RESEARCH ABSTRACTS. - ISSN 1607-7962. - ELETTRONICO. - 12:(2010), pp. 3980-3980.

Availability:

The webpage <https://hdl.handle.net/2158/406291> of the repository was last updated on

Terms of use:

Open Access

La pubblicazione è resa disponibile sotto le norme e i termini della licenza di deposito, secondo quanto stabilito dalla Policy per l'accesso aperto dell'Università degli Studi di Firenze (<https://www.sba.unifi.it/upload/policy-oa-2016-1.pdf>)

Publisher copyright claim:

La data sopra indicata si riferisce all'ultimo aggiornamento della scheda del Repository FloRe - The above-mentioned date refers to the last update of the record in the Institutional Repository FloRe

(Article begins on next page)



Slope instability mapping around L'Aquila (Abruzzo, Italy) with Persistent Scatterers Interferometry from ERS, ENVISAT and RADARSAT datasets

Gaia Righini, Sara Del Conte, Francesca Cigna, and Nicola Casagli

University of Firenze, Department of Earth Sciences, Firenze, Italy (gaia.righini@unifi.it)

In the last decade Persistent Scatterers Interferometry (PSI) was used in natural hazards investigations with significant results and it is considered a helpful tool in ground deformations detection and mapping (Berardino et al., 2003; Colesanti et al., 2003; Colesanti & Wasowski, 2006; Hilley et al., 2004).

In this work results of PSI processing were interpreted after the main seismic shock that affected the Abruzzo region (Central Italy) on 6th of April 2009, in order to carry out a slope instability mapping according to the requirement of National Department of Civil Protection and in the framework of the Landslides thematic services of the EU FP7 project 'SAFER' (Services and Applications For Emergency Response – Grant Agreement n° 218802).

The area of interest was chosen in almost 460 km² around L'Aquila according the highest probability of reactivations of landslides which depends on the local geological conditions, on the epicenter location and on other seismic parameters (Keefer, 1984).

The radar images datasets were collected in order to provide estimates of the mean yearly velocity referred to two distinct time intervals: historic ERS (1992-2000) and recent ENVISAT (2002-2009), RADARSAT (2003-2009); the ERS and RADARSAT images were processed by Tele-Rilevamento Europa (TRE) using PS-InSAR(TM) technique, while the ENVISAT images were processed by e-GEOS using PSP-DIFSAR technique.

A pre-existing landslide inventory map was updated through the integration of conventional photo interpretation and the radar-interpretation chain, as defined by Farina et al. (2008) and reported in literature (Farina et al. 2006, Meisina et al. 2007, Pancioli et al., 2008; Righini et al., 2008, Casagli et al., 2008, Herrera et al., 2009). The data were analyzed and interpreted in Geographic Information System (GIS) environment.

Main updates of the pre-existing landslides are focusing on the identification of new landslides, modification of boundaries through the spatial radar interpretation and the assessment of the state of activity, intended as defined by Cruden and Varnes (1996). The information coming from the radar interpretation is the basis to evaluate the state of activity and the intensity of slow landslides.

Two main situations can occur: the presence of PS within the already mapped landslides, and the presence of PS outside the previous mapped area resulting often in new landslides.

The analysis of PSI data allowed to map 57 new landslides and gave information on 203 (39%) landslides mapped of the pre-existed PAI while the updated Landslide Inventory Map has 579 landslides totally: thus EO data did not give any additional information on 319 landslides of the pre-existing inventory map. Considering the 203 updated landslides, the modifications concern 155 phenomena while 48 are confirmed: the modifications are related to the boundary and/or the state of activity and the typology. All the new landslides added are considered active.

It is worth noting that almost all the landslides where the state of activity is changed from dormant (or stabilized) to active involve urban areas and the road network where the reliability of radar benchmarks is higher.

Radar satellite data were in particular very useful to map slow superficial movements named as "creep" that are widespread in the slopes around L'Aquila: the typical velocity is few centimeters per year which is perfectly suited to the capability of multi-interferometric techniques for ground deformation detection.

References:

Berardino, P., Costantini, M., Franceschetti, G., Iodice, A., Pietranera, L., Rizzo, V. (2003). use of differ-

ential SAR interferometry in monitoring and modelling large slope instability at Maratea (Basilicata, Italy). *Engineering Geology*, 68 (1-2), 31 - 51.

Casagli N., Colombo D., Ferretti A., Guerri L., Righini G. (2008)- Case Study on Local Landslide Risk Management During Crisis by Means of Remote Sensing Data. *Proceedings of the First World Landslide Forum*. 16-19 November 2008 Tokyo Japan, 125-128.

Colesanti, C., Ferretti, A., Prati, C., Rocca, F. (2003). Monitoring landslides and tectonic motions with the Permanent Scatterers Technique. *Engineering Geology*, 68, 3 - 14.

Colesanti, C., Wasowski, J., (2006). Investigating landslides with satellite Synthetic Aperture Radar (SAR) interferometry. *Engineering Geology*, 88 (3 - 4), 173 - 199.

Cruden, D.M., Varnes, D.J. (1996). Landslide types and processes. In: Turner AK, Schuster RL (eds) *Landslides investigation and mitigation*, Special Report 247. Transportation Research Board, National Research Council, Washington, DC, 36 - 75.

Farina P., Colombo D., Fumagalli A., Marks F., Moretti S. (2006) - Permanent Scatterers for landslide investigations: outcomes from the ESA-SLAM project. *Engineering Geology*, v. 88, p.200-217.

Farina P., Casagli N., Ferretti A. (2008) - Radar-interpretation of InSAR measurements for landslide investigations in civil protection practices. *First North American Landslide Conference*, June 3-8, 2007. Vail, Colorado, pp. 272-283.

Hilley, G.E, Burgmann, R., Ferretti, A., Novali, F., Rocca, F. (2004). Dynamics of slow-moving landslides from Permanent Scatterer analysis. *Science*, 304 (5679), 1952 - 1955.

Herrera G., Davalillo J.C., Mulas J., Cooksley G., Monserrat O., Pancioli V. (2009) - Mapping and monitoring geomorphological processes in mountainous areas using PSI data: Central Pyrenees case study *Nat. Hazards Earth Syst. Sci.*, 9, 1587–1598,

Meisina C., Zucca F., Fossati D., Ceriani M, Allievi J. (2006) - Ground deformations monitoring by using the Permanent Scatterers Technique: the example of the Oltrepo Pavese (Lombardia, Italy), *Engineering Geology*, 88, 240-259.

Pancioli V., Farina P., (2007) - Analisi dei fenomeni franosi con dati InSAR satellitari: primi risultati del progetto ESA-TerraFirma. *Giornale di Geologia Applicata* 6-A: 101-102.

Righini, G., Del Ventisette, C., Costantini, M., Malvarosa, F., Minati, F. (2008). Space-borne SAR Analysis for Landslides Mapping in the Framework of the PREVIEW Project. *Proceedings of the First World Landslide Forum*, Tokyo Japan, 505-506.