UNIVERSITÀ
DEGLI STUDI
FIRENZE

FLORE

Repository istituzionale dell'Università degli Studi di Firenze

Occurrence of organic microcontaminants in the wastewater treatment process.

Questa è la Versione finale referata (Post print/Accepted manuscript) della seguente pubblicazione:

Original Citation:

Occurrence of organic microcontaminants in the wastewater treatment process. A mini review / N. Ratola; A. Cincinelli; A. Alves; A. Katsoyiannis. - In: JOURNAL OF HAZARDOUS MATERIALS. - ISSN 0304-3894. - STAMPA. - 239-240:(2012), pp. 1-18. [10.1016/j.jhazmat.2012.05.040]

Availability:

This version is available at: 2158/647353 since: 2016-11-18T22:22:37Z

Published version:

DOI: 10.1016/j.jhazmat.2012.05.040

Terms of use:

Open Access

La pubblicazione è resa disponibile sotto le norme e i termini della licenza di deposito, secondo quanto stabilito dalla Policy per l'accesso aperto dell'Università degli Studi di Firenze (<https://www.sba.unifi.it/upload/policy-oa-2016-1.pdf>)

Publisher copyright claim:

(Article begins on next page)

This article appeared in a journal published by Elsevier. The attached copy is furnished to the author for internal non-commercial research and education use, including for instruction at the authors institution and sharing with colleagues.

Other uses, including reproduction and distribution, or selling or licensing copies, or posting to personal, institutional or third party websites are prohibited.

In most cases authors are permitted to post their version of the article (e.g. in Word or Tex form) to their personal website or institutional repository. Authors requiring further information regarding Elsevier's archiving and manuscript policies are encouraged to visit:

<http://www.elsevier.com/copyright>

Contents lists available at SciVerse ScienceDirect

Journal of Hazardous Materials

journal homepage: www.elsevier.com/locate/jhazmat

Occurrence of organic microcontaminants in the wastewater treatment process. A mini review

Nuno Ratola^{b,c}, Alessandra Cincinelli^{b,d}, Arminda Alves^c, Athanasios Katsoyiannis^{a,b,*}

^a Norwegian Institute for Air Research, FRAM – High North Research Centre on Climate and the Environment, NO-9296 Tromsø, Norway

^b Lancaster Environment Centre, Lancaster University, LA14YQ, Lancaster, UK

^c LEPAE, Department of Chemical Engineering, Faculty of Engineering, University of Porto, Rua Dr. Roberto Frias, 4200-465 Porto, Portugal

^d Department of Chemistry, University of Florence, Via della Lastruccia, 3, 50019 Sesto Fiorentino, Florence, Italy

HIGHLIGHTS

- Ten-fold increase in the number of papers on PPCPs in WWTPs in ten years.
- Wastewater analysis can help tackle societal problems.
- PFCs in WWTPs present negative removal rates.

ARTICLE INFO

Article history:

Received 11 February 2012

Received in revised form 9 May 2012

Accepted 10 May 2012

Available online 18 May 2012

Keywords:

Wastewater

Pharmaceuticals

Illicit drugs

Doping substances

Organophosphates

PFCs

ABSTRACT

A wastewater treatment plant may receive various types of wastewater namely, urban, industrial, agricultural, washout from the streets, wet or/and dry atmospheric deposition. As such, scientists have detected in wastewaters all major categories of pollutants like persistent organic pollutants (POPs), polycyclic aromatic hydrocarbons (PAHs) and pesticides, but also substances that are widely used as pharmaceuticals and cosmetics, classified as “PPCPs” (pharmaceuticals and personal care products). Finally, the latest categories of compounds to be looked upon in these types of matrices are illicit drugs (drugs of abuse, like cocaine, etc.) and doping substances.

This review article summarises major categories of organic microcontaminants that have been detected in wastewaters and studies their fate during the wastewater treatment process. Occurrence of these compounds in the influents and effluents are reported, as well as percents of removal, mass balances and phase distributions.

© 2012 Elsevier B.V. All rights reserved.

1. Introduction

Wastewater treatment plants (WWTPs) were initially designed to remove/decrease conventional pollution parameters (BOD₅, COD, total suspended solids, etc.) from the wastewater stream, so that the final effluent did not constitute a new source of pollution for the water body receiving it. However, it was soon found out that the wastewater organic load included high levels of a variety of hazardous organic pollutants and thus additional treatment steps and control measures became necessary. The quality of wastewater varies according to what types of influents the WWTP may receive, such as domestic wastewater, dry and wet atmospheric deposition, urban runoff containing traffic related pollution or agri-

cultural runoff and the range of contaminants is even broader when industrial effluents are also included in the input wastewater [1–4].

WWTPs are also called “biological treatments” due to the secondary treatment step, during which the wastewater comes in contact with “activated sludge” and conventional contaminants are removed by means of biological degradation. Whilst this is the case for most of the organic load, for modern organic contaminants such as persistent organic pollutants (POPs), brominated flame retardants (BFRs), fluorinated compounds (PFCs) or pharmaceuticals among others, it has been shown that the biological treatment is not so efficient in their removal. These chemicals are not completely degraded and are either removed by sorption and deposition to the final sludge, by volatilisation, or by discharge onto a surface water body, if they remain in the wastewater effluent stream [7]. This last fraction is the most concerning, since it has been shown to be of relevant toxicity, readily bioavailable to living organisms, able to enter the food chain and hence ultimately exposing humans [5,6]. One of the most important factors that tend to keep organic microcontaminants in the wastewater stream is the dissolved organic carbon

* Corresponding author at: Norwegian Institute for Air Research, FRAM – High North Research Centre on Climate and the Environment, NO-9296 Tromsø, Norway. Tel.: +47 77750386; fax: +30 2312201944.

E-mail address: aak@nilu.no (A. Katsoyiannis).

Fig. 1. Number of publications per year studying PPCPs in WWTPs.

Source: SCOPUS™ Database.

(DOC) [7]. In particular, and due to its affinity with organic microcontaminants, DOC acts as an antagonist to sorption on particles and that way keeps organic microcontaminants in the wastewater stream.

In recent years, scientists have been considering as microcontaminants some compounds (or classes of compounds) that until some years ago were deemed safe or broadly supposed to be totally biodegradable, such as personal care products, pharmaceuticals or chemicals like caffeine, benzotriazole, etc. [8–13]. As a result of their broad usage, these microcontaminants have been detected in concentrations up to several $\mu\text{g/L}$ in WWTP effluents and in surface waters.

Bearing in mind the aforementioned information, the scope of this paper is to present concentration levels, to describe the fate and trends and to discuss the respective implications of new categories of microcontaminants detected in wastewaters/WWTPs. These classes of chemicals include (a) pharmaceuticals and personal care products (b) illicit drugs (c) prohibited doping substances (d) persistent organic pollutants (e) perfluorinated compounds.

2. Methodology

Given the large number of studies present in literature, this study goes over some of the most important characteristics that govern the fate of OPs during the wastewater treatment process and presents interesting scientific aspects that derive from the chemical analysis of wastewaters for the aforementioned compounds.

3. Discussion

3.1. Pharmaceuticals and personal care products (PPCPs)

It has been known for over 20 years that pharmaceuticals and personal care products (PPCPs) enter into the environment through individual human activity and as residues from manufacturing, agribusiness, veterinary use, and hospitals and community use. Individuals may add PPCPs to the environment through waste excretion or bathing, as well as by directly disposing of unused medications into septic tanks, sewers, or trash containers. Their presence has been identified and quantified in WWTP effluents [14], surface waters [15], drinking water [150], groundwater [151], biosolids [152], agricultural manures [153] and biota [154]. With hundreds of different PPCPs in the market (see Table 1), WWTPs represent a key potential point source to the aquatic environment, but at the same time a major opportunity for centralised removal processes. This justifies the increasing number of studies dealing with pharmaceuticals in WWTPs in the last decade (Fig. 1). Summarizing research results in this area is not a simple task, given the large number of PPCPs found in WWTPs. The most common belong to the categories of antibiotics, analgesic

and anti-inflammatory. However, other groups include diuretics, antibiotics, antidiabetics, anticoagulants, psychiatric drugs, lipid regulators, histamine H2 antagonists [14,15], anti-epileptic drugs [15,16], antifongics, antineoplasics, disinfectants, antidepressants, antiseptics, hormones, vasodilators [15], antifungics, vasodilators, barbiturates, anticancers, anticonvulsants [17], anti-hypersensitives and antilipemics [18]. Recently, a review by Miega et al. [15] presented the concentrations of PPCPs in WWTP influents and effluents, their removal efficiency and their loads to the aquatic environment. Their database covered 184 PPCPs from 117 scientific publications until 2008.

It is difficult to discuss typical concentration levels (Table 1) of PPCPs as these can range from hundreds of pg/L up to hundreds of $\mu\text{g/L}$ [13,15,19–25], depending on the target PPCP and the type of wastewater. Other important factors that play a role in the occurring levels are the types of products that can be found in the pharmaceutical market in each country, or the possibility in some countries to purchase medicines without a medical prescription [15]. As a matter of fact, reported average influent concentrations ranging between 0.1 ng/L for hormones and 34 $\mu\text{g/L}$ for naproxen, whilst naproxen in a study by Nakada et al. [26] occurred in concentrations of only a few ng/L . If specific circumstances occur, the concentration levels of PPCPs in WWTPs can increase even further, to tens of mg/L . Such a case was the outbreak of the avian influenza, which led to concentrations of 20 mg/L for oseltamivir carboxylate in WWTPs with low flow and high population equivalents [20]. In the same study, it is stated that under normal conditions, the majority of PPCPs do not exhibit seasonality, but for some like antibiotics, temporal variation is observed due to increased winter usage.

Individual PPCPs have also distinct chemical and physical properties that suggest potentially different mechanisms and locations for removal/reduction in a WWTP. PPCPs can have octanol–water partition coefficients (K_{ow}) or water solubility (WS) values that vary up to 7–8 orders of magnitude. As an example, $\log K_{ow}$ of iopromide: -2.05 and $\log K_{ow}$ of mefenamin acid: 5.12 [23,27], or WS of roxithromycin: 0.0189 mg/mL and WS of diclofenac: 50 mg/mL . Many of the PPCPs are ionisable chemicals and it may not be appropriate to assess their lipophilicity based only on the K_{ow} value. Wells [171,172] addressed the latter issue underlining the value of using a different physical–chemical property which takes into account both hydrophobicity and ionogenicity (especially for the cases where $\text{pK}_a < \text{pH}$). Thus, Wells [171,172] suggested that the pH-dependent *n*-octanol–water partition coefficient D_{ow} should be used. High K_{ow} (or D_{ow}) values mean that PPCPs tend to sorb onto suspended particles and end up in the sewage sludge, whereas compounds with low K_{ow} and high WS are expected to remain in the wastewater stream and, if resistant against microbial degradation, to be discharged with the final effluents. Removal rates can also vary largely between various contaminants. For example diclofenac showed low removal rates ($21.8 \pm 28.5\%$), whereas ibuprofen showed a removal of $99.1 \pm 1.8\%$ [16]. Interestingly, in many cases PPCP loads increase during the wastewater treatment. Thus, diclofenac showed a raise of 105% in a sewage treatment plant of Sweden [28], and up to 300% in a WWTP in Korea [24]. In the latter study, other PPCPs showing a negative removal rate were acetylsalicylic acid, naproxen, ketoprofen and clofibrac acid. A possible explanation for negative removal rates is the influent–effluent mismatching, or the formation of “conjugated compounds” throughout the treatment steps, like for example happens with glucuronic acid [172]. A review by Onesios et al. [17] reported removal rates for a very large number of PPCPs. Authors evidenced that removal rates may vary considerably even for the same PPCP, and inter-comparisons are most of the times problematic, due to different definitions of removal, decrease or elimination rates, but also to different sampling strategies applied (integrated versus grab samples). In addition, the different treatment approaches described in

Table 1
PPCP concentrations in wastewaters (ng/L).

[illegible]

Table 1 (Continued)

	MW	log K_{ow}	pK _a	Influent (ng/L)	Effluent (ng/L)	Removal (%)	Reference
				900	170		[24]
				315	103		[24]
				21 (11–36)	<10		[27]
Chloramphenicol	323.13	0.92	13.59	14 (<4–319)	<6		[157]
Tetracyclin	444.43	–1.33	3.3	457 (240–790)	282 (50–850)		[15]
Hormones							
Estrone	270.4	3.13	10.34	47 (32–70)	6 (0–24)	87.1	[18]
				67.2 (2.4–670)	20.9 (0.6–95)		[15]
				32.0 ± 6.0			[28]
				150 ± 16			[28]
Estriol	288.4	2.8	10.38	415 (125–802)	0	100	[18]
				115 (14.6–660)	13.1 (0.4–275)		[15]
Estradiol	272.4	4.01	10.46	4 (0–4)	0	100	[18]
				26.5 ± 6.0			[28]
				17.0 ± 5.0			[28]
17a-estradiol				7.4 (1.5–17.2)	0.8 (0.1–3.1)		[15]
17b-estradiol				22.2 (2.5–125)	2.8 (0.3–30)		[15]
Analgesics/ antiinflammatories							
Acetaminophen/ paracetamol	151.17	0.46	9.04	7460 (3540–10,234)	10 (0–27)	99.9	[18]
				13,200 (1340–51,900)	652		[23]
				23,600 (804–85,200)	ND		[23]
				25,500 (271–63,100)	ND		[23]
				29,100 (40–104,000)	431		[23]
				3410	ND		[24]
				9610	ND		[24]
				10,100	ND		[24]
				62,600	ND		[24]
				48,100	ND		[24]
				9500	ND		[24]
				5950	ND		[24]
				7010	ND		[24]
				3130	ND		[24]
				8270	ND		[24]
				4190	6760		[24]
					293		[156]
				211,380 (68,107–482,687)	11,733 (1826–24,525)		[157]
				80,000 (5530–292,000)			[15]
				80,000 (37,000–130,000)	<50		[27]
Diclofenac	296.15	0.7	4.2	131 (59–243)	24 (13–49)	81.4	[18]
				69 (26–257)	98 (33–142)		[157]
				1340 (105–4110)	680 (350–1950)		[15]
				237 (94–523)	191 (52–1760)		[23]
				ND	186		[23]
				1920 (28–6880)	161 (46–221)		[23]
				181,000 (160,000–203,000)	7560 (457–19,200)		[23]
				107–981	37–176		[158]
				42	33		[24]
				5	17		[24]
				39	29		[24]
				16	29		[24]
				14	18		[24]
				12	46		[24]
				20	29		[24]
				11	25		[24]
				14	2		[24]
				2	5		[24]
				ND	ND		[24]
					1090		[156]
				859 (50–4200)			[25]
				220 (140–280)	<10		[27]
				700 ± 120			[28]
				380 ± 10			[28]
				210 ± 100			[28]
Ibuprofen	206.23	3.97	4.9	2265 (1599–2853)	40 (15–75)	98.2	[18]
				1681 (968–2986)	263 (131–424)		[157]
				14,600 (170–83,500)	1960 (20–24,600)		[15]
				69,700 (3730–353,000)	4130 (<LOD–26,500)	87	[159]
				84,400 (<LOD–294,000)	6690 (<LOD–40,200)	84	[159]
				105,000 (<LOD–319,000)	1160 (<LOD–55,000)	80	[159]
				115,000 (<LOD–603,000)	76,200 (<LOD–48,200)	87	[159]

Table 1 (Continued)

MW	log K_{ow}	pK _a	Influent (ng/L)	Effluent (ng/L)	Removal (%)	Reference
			1100	ND		[24]
			1170	ND		[24]
			982	ND		[24]
			852	ND		[24]
			612	ND		[24]
			73	ND		[24]
			1120	ND		[24]
			1040	ND		[24]
			1020	ND		[24]
			ND	ND		[24]
			213	238		[24]
				2400		[156]
			3200 (<LOD–11,900)			[25]
			11,000 (3900–15,000)	<10		[27]
			14,300 ± 130			[28]
			8800 ± 100			[28]
			10,800 ± 100			[28]
Ketoprofen 254.29	3.12	4.5	202 (81–286)	12 (0–37)	94.2	[18]
			28 (<4–119)	–		[157]
			1030 (800–5700)	325 (400–1620)		[15]
			1580 (<LOD–5520)	860 (<LOD–2270)	52	[159]
			1740 (<LOD–6470)	800 (<LOD–1950)	56	[159]
			1910 (<LOD–8560)	820 (<LOD–3920)	72	[159]
			2070 (<LOD–5700)	880 (<LOD–2030)	58	[159]
			114	ND		[24]
			83	ND		[24]
			226	35		[24]
			49	41		[24]
			44	ND		[24]
			81	ND		[24]
			50	ND		[24]
			18	ND		[24]
				2980		[156]
			561 (<LOD–1520)			[25]
Naproxen 230.27	3.18	4.2	2584 (1360–5033)	111 (37–166)	95.7	[18]
			838 (400–1457)	370 (234–703)		[157]
			25,400 (1790–611,000)	1890 (170–33,900)		[15]
			3810 (480–12,500)	250 (21–740)		[23]
			3170 (306–6040)	309 (248–370)		[23]
			59,700 (410–206,000)	13,300 (361–39,300)		[23]
			4830 (2020–8500)	2740 (540–5090)	43	[159]
			8070 (2030–52,900)	1640 (220–3520)	71	[159]
			4690 (1630–27,400)	2180 (830–3640)	48	[159]
			4280 (1140–9100)	1670 (290–4280)	60	[159]
			1210	254		[24]
			827	104		[24]
			962	114		[24]
			823	57		[24]
			487	48		[24]
			524	138		[24]
			532	ND		[24]
			451	183		[24]
			565	ND		[24]
			761	ND		[24]
			278	77		[24]
				1740		[156]
			335 (<LOD–1550)			[25]
			20,200 ± 210			[28]
			9300 ± 100			[28]
			6600 ± 110			[28]
Mefenamic acid 241.3	5.12	4.2	121 (55–328)	153 (44–392)	–26.30	[18]
			205 (<20–1269)	61 (<5–222)		[157]
			1730 (136–3200)	1140 (900–2400)		[15]
			1900 (232–8810)	385 (68–1360)		[23]
			ND	167		[23]
			14,200 (329–36,400)	ND		[23]
			119	32		[24]
			52	43		[24]
			192	68		[24]
			42	53		[24]
			127	83		[24]
			121	11		[24]
			92	21		[24]
			55	25		[24]

Table 1 (Continued)

	MW	log K_{ow}	pK _a	Influent (ng/L)	Effluent (ng/L)	Removal (%)	Reference
Aspirin	180.15	1.19	3.49	61	3		[24]
				23	6		[24]
				53 (<LOD–120)			[25]
				664 (485–2042)	27 (<3–85)		[157]
Acetyl salicylic acid	180.15	1.29		5866 (1479–18,479)	164 (<1–497)		[157]
				212,000 (16,000–606,000)	2500 (300–4800)		[15]
				176,000 (3090–1,407,000)	7240 (2340–12,100)		[23]
				313,000 (41,800–1,030,000)	89,500 (1000–193,000)		[23]
				126,000 (1540–384,000)	507 (396–618)		[23]
				551,000 (3850–1,731,000)	25,200 (2830–47,600)		[23]
				2040	ND		[24]
				11,100	9		[24]
				7640	10		[24]
				3160	ND		[24]
				2610	27		[24]
				7600	6		[24]
				3910	10		[24]
				3970	ND		[24]
				11,100	32		[24]
				9780	30		[24]
				2670	78		[24]
Codeine	299.36	1.28	8.21	10,321 (1732–32,295)	5271 (2940–15,593)		[157]
Tramadol	263.37	2.51	9.41	36,750 (8505–89,026)	43,813 (24,132–97,616)		[157]
Dextropropoxyphene		4.18		27.3 (22–33)	52.3 (37–64)		[15]
Antiepileptic Carbamazepine	263.27	2.45	3.19	72 (43–127)	55 (40–74)	23.1	[18]
					437 ± 117		[160]
				1694 (709–2930)	2499 (644–4596)		[157]
				968 (100–1900)	674 (150–2300)		[15]
				1920 (95–21,600)	1750 (208–21,000)		[23]
				167 (40–399)	2430 (128–10,200)		[23]
				827 (18–6080)	3560 (241–14,400)		[23]
				10,100 (35–19,100)	51,700 (61–150,000)		[23]
				530 (<LOD–3780)	580 (<LOD–1180)	11	[159]
				470 (<LOD–2100)	610 (150–1290)	7	[159]
				410 (<LOD–1310)	490 (<LOD–840)	7	[159]
				490 (<LOD–2150)	560 (150–1550)	8	[159]
					(233–1061)		[158]
				258	180		[24]
				327	188		[24]
				481	175		[24]
				214	140		[24]
				290	183		[24]
				450	170		[24]
				311	243		[24]
				338	235		[24]
				105	173		[24]
				103	96		[24]
				207	36		[24]
				419 (120–1550)			[25]
				230 (130–440)	1 (<10–12)		[27]
Gabapentin	171.24	–1.10		15,034 (2059–37,426)	15,747 (3001–42,611)		[157]
Antilipidemic Clofibric acid	214.5	2.57	3.2	28 (0–65)	2 (0–6)	93.6	[18]
				19 (<1–57)	15 (<1–75)		[157]
				294 (15–651)	150 (42–230)		[15]
				33	8		[24]
				ND	6		[24]
				ND	35		[24]
				55	35		[24]
				ND	4		[24]
					30		[156]
				25.0 ± 3.0			[28]
				12.5 ± 7.0			[28]
				17.0 ± 6.5			[28]
Gemfibrozil	250.34	4.77	4.7	222 (101–318)	17 (9–26)	92.3	[18]
				1630 (700–3000)	564 (60–1340)		[15]
				21	ND		[24]
				14	ND		[24]
					520		[24]
				377 (<LOD–1700)			[25]

Table 1 (Continued)

	MW	log K_{ow}	pK _a	Influent (ng/L)	Effluent (ng/L)	Removal (%)	Reference
Bezafibrate	361.82		14.75	420 (209–1391) 2440 (100–7600) 65 (<LOD–260)	231 (<85–667) 816 (20–4800)	92	[157] [15] [25]
Simvastatin	418.57			115 (<7–798)	5 (<3–20)	38	[157]
Stimulant Caffeine	194.19	−0.07	10.4	2349 (3217–1608) 2400 6170 7310 4860 3270 1950 1920 2500 1160 2190 56,100 80,000 (54,000–120,000)	18 (0–60) 24 ND ND ND ND ND ND ND ND ND ND 17 (<10–50)	98.2	[18] [24] [24] [24] [24] [24] [24] [24] [24] [24] [24] [24] [27]
Nicotine	162.23		3.1		373 (72–1706) 235 (93–755) 430 (76–3857) 213 (75–253) 538 (101–3249)		[161] [161] [161] [161] [161]
Antihypersensitive Atenolol	266.3	0.16	9.6	7801 (5113–11,239) 12,913 (3090–33,106) 30 1880 (<LOD–7560)	2772 (261–5911) 271 ± 91 2870 (1260–7602) 154 (10–380) 1094	64.5	[18] [160] [157] [15] [156] [25]
Metoprolol	267.3	2.15	9.6	4 (2–6) 75 (39–117) 160 953 (<LOD–4680)	3 (3) 274 ± 192 69 (35–130) 338 (10–688) 13	23	[18] [160] [157] [15] [156] [25]
Solatol				221 (<LOD–1080)	274 ± 192		[160] [25]
Acebutolol	336.43				2 ± 2		[160]
Propanolol	259.34			557 (125–1962) 74.7 (50–119)	265 (121–405) 341 (10–615) (16–135)		[157] [15] [158]
Antiseptic (dinfectant) Triclosan	289.6	4.76	7.8	547 (247–785) 380	112 (79–149) 150 (70–430)	99.6	[18] [15]
Diuretics Furosemide	330.74			1476 (836–5111)	1161 (583–1956)		[157]
Antidepressant Amitriptyline	277.40			1249 (341–5143)	197 (53–357)		[157]
Personal care products Galaxolide	258.4	5.9		2510 (790–4443) 1941 9710 (+5090) 16,600 (+10700)	642 (451–1080) 695 32–3750 10–25,947		[15] [162] [163] [161]
Tonalide	258.4	5.7		990 (210–1690) 583 5970 (+3880) 12,500 (+7350)	162 (144–200) 212 24–2670 2.1–2151		[15] [161] [163] [161]
Celestoide	244.4				ND-92		[161]
Benzophenone-1	182.2	3.15		258 (51–700)	12 (<2–38)		[157]
Benzophenone-2				194 (61–403)	4 (<13–13)		[157]
Benzophenone-3				1195 (<104–3975)	22 (<80–223)		[157]
Benzophenone-4				4152 (2218–6084)	3370 (<10–6325)		[157]
Methylparaben	152.2	2.0		11,601 (4550–30 688)	<3–36 (9)		[157]

Table 1 (Continued)

	MW	log K_{ow}	pK _a	Influent (ng/L)	Effluent (ng/L)	Removal (%)	Reference
Ethylparaben	166.2	2.5		2002 (715–3312)	4 (<0.6–43)		[157]
Propylparaben	180.2	2.9		3090 (820–8286)	26 (<1–84)		[157]
Butylparaben	194.2	3.5		723 (274–1595)			[157]
Vasodilator							
Pentoxifyllin	278.31				533 (500–600)		[15]

each study render these comparisons less useful. As a matter of fact, Onesios et al. [17] reported removal rates for diclofenac between 1 and 94%, for a variety of treatment systems, whereas in many studies it was not reported.

The elimination efficiency of PPCPs in WWTPs can be further complicated by biological transformations, mixture effects, hydraulic and temperature variations and the combination of treatment processes. It is however known that this efficiency increases with higher hydraulic retention times (HRT) [155]. In the last few years, the application of more advanced treatment processes such as ozonation, activated carbon, and tight membrane filtration are receiving considerable attention, although studies addressed to a better understanding of removal in conventional treatments (primary, secondary and tertiary) remain active. The use of advanced oxidation technologies increases the formation of intermediate degradation products that may be more toxic than the parental ones. Further analytical and toxicological research studies are needed to increase the knowledge in this area. Lin et al. [29] reported that the combined ozone systems (O_3/H_2O_2) contribute to an enhancement in the removal of sulphonamide and macrolides antibiotics. Four antibiotics (sulfamethoxazole, sulfamethoxine, sulfamethazine and trimethoprim) and four non-steroidal anti-inflammatory drugs (acetaminophen, ibuprofen, retoprofen and naproxen) were also successfully removed using extended sludge age biological system [30]. However, the same study showed that the removal efficiency is strongly related to the initial influent concentration of each target compound. The combination of a UV/TiO₂ system was reported to be highly efficient to the complete elimination of naproxen, clofibric acid and carbamazepine [31] in addition to ofloxacin [32], and a removal efficiency ranging from 12 to 80% was reported for iomeprol [33,34]. Moreover, the use of UV/H₂O₂ systems in the presence of humic acids resulted in very effective removal of carbamazepine and diclofenac [35] and clofibric acid [36]. The capacity of granular activated carbon (GAC) in comparison with other adsorbents was tested to remove estrone and 17 α -estradiol [37], showing that the elimination rate increased at pH above 8 and adsorption capacity of GAC decreased by the presence of surfactants or humic acids. Maniero et al. [38] investigated the degradation of natural (17 β -estradiol) and synthetic (17 α -ethinylestradiol) estrogens (pure or in the mixture) and the cease of estrogenic activity by the ozonation and O_3/H_2O_2 process at three different pH levels (3, 7 and 11). Both these processes were effective in eradicating the estrogens from aqueous solutions, for all ozone doses and pH values in question. Senta et al. [39] evaluated membrane bioreactors (MBRs), nanofiltration, reverse osmosis and ozonation, as well as their combinations, for the removal of antimicrobials including sulfonamides, fluoroquinolones, macrolides and trimethoprim from a synthetic wastewater which simulated highly contaminated industrial effluents. MBR system was only efficient for the elimination of sulfonamides whereas nanofiltration and reverse osmosis achieved high elimination rates, yet producing a highly contaminated concentrate.

Many studies have also reported the occurrence of PPCPs in sewage sludge. A review by Diaz-Cruz et al. [40] summed up the

occurrence of 12 PPCPs (only 8 at detectable levels), yet with considerably variable concentrations. According to their summary, limits of detection for PPCPs under different techniques can be at the sub- μ g/kg level, and concentrations of up to 1500 μ g/kg have been reported (triclosan from a WWTP in Galicia, Spain, [40,41]). Triclosan occurred at even higher levels in the sludge from the major WWTP of Athens, Greece, reaching 1790 μ g/kg [42]. This compound has a log K_{ow} of 4.8 and a pK_a of 7.9, which at wastewater conditions (pH around 7) can be considered a hydrophobic compound prone to sorption onto the sludge. The concentrations of PPCPs detected in sewage sludge reflect their use in the society [40], although the influent wastewater is a better indicator, especially for hydrophilic and water soluble PPCPs that are not likely to be detected in sludge. According to Horsing et al. [43], who studied the sorption of 75 common PPCPs, only 14 were found to have strong affinity with particles/sludge, whereas for 37 of them, more than 80% of their predicted occurrence would be in the liquid phase. In that study, pH was also identified as an important factor for the partition to the sludge. Other parameters affecting the sewage concentration of PPCPs can be the sludge retention time or the biosolids acclimatisation [44,45].

3.2. Illicit drugs (IDs)

In the last few years, the scientific community started paying more attention to the occurrence of drugs of abuse or illicit drugs (IDs) in various environmental compartments. The number of studies dealing with IDs in WWTPs is not as large as for PPCPs, but is increasing continuously. Compounds of interest in this category belong to the groups of stimulants, hallucinogens, opioids, dissociative anaesthetics, etc. [46], whilst key target chemicals are cocaine (COC), heroin, nicotine, amphetamine, methamphetamine, opiates or cannabis, among others, and their metabolites, e.g. benzoylecgonine (BE), ecgonine methyl ester, norbenzoylecgonine, norcocaine and cocaethylene [13,46–52]. For compounds like nicotine and caffeine, a study in Spain has shown that average concentrations of 13 and 23 μ g/L are detected in influent wastewaters, respectively, and that the mean values for effluent wastewaters can be as high 2.7 and 4.4 μ g/L, respectively. Instead, for the stronger narcotic (COC), the highest concentration observed to date was in the influent of a WWTP in Barcelona (4.7 μ g/L) [51]. The concentrations of IDs in the influents of WWTPs can reflect both societal habits and the financial situation. As a matter of fact, their levels have been found to increase during weekends [50,53,54], or after the “Street Parade” event in Zurich [55]. MDMA (an amphetamine-type drug) was found to be more abundant on Sundays and Tuesdays, in WWTPs from Paris [50]. Regarding the temporal trends of IDs, the existing dataset is still insufficient for such an assessment. [56]. According to the latter study that took place in Italy, there is a decreasing trend in the consumption of expensive IDs and a simultaneous increase in the less expensive ones.

The important implication of the analysis of IDs in WWTPs is the back estimation of equivalent drug users and consumption. This has been applied by many scientific groups and, recently, a review has been published on this topic [48].

Table 2

Cocaine and benzoylecgonine concentrations in wastewaters (ng/L).

	Cocaine		Benzoylecgonine		Reference
	Influent	Effluent	Influent	Effluent	
WWTPs in UK (7)	70.9	29.2	243.1	115.9	[46]
WWTP Paris 1	4.8–52.6	ND-7	64.0–175.6	15.9–25.4	[50]
WWTP Paris 2	67.2–282	ND-20.7	147.2–849.2	82.0–149.0	
WWTP Paris 3	12.0–53.7	1.2–5.3	136.1–218.0	14.5–36.3	
WWTP Paris 4	32.7–99.2	ND-3.2	129.4–303.1	7.9–18.2	
WWTP Oslo	86 (35–166)		273 (121–669)		[60]
WWTP Geneva	NQ-1928		101–1788		[103]
WWTP Luzern	NQ-297		244–1040		
WWTP Basel	177–262		872–1299		
WWTP Berne	159–336		522–1132		
WWTP Zurich	406–1109		802–2400		
WWTP Back River	2.66 ± 0.005		9.31 ± 0.17		[104]
WWTP, Prison in Catalonia	128 ± 94 (max. 462)		556 ± 291 (max. 1760)		[105]
WWTP Milan	255		712		[54]
WWTP Como	98		380		
WWTP Cagliari	138		316		
WWTP Olbia	131		337		
WWTP Sassari	48		149		
WWTP Nuoro	55		153		
WWTP Chicago	868		1553		
WWTP Villaseca	160–2486	NQ-9	1169–3336	1–42	[53]
WWTP Canada 1	209–823		287–1488		[52]
WWTP Canada 2	475–776		658–2624		
WWTP Canada 3	487–656		588–722		

One of these approaches is the “sewage epidemiology”, which uses wastewater concentrations for the abovementioned purpose. The concept of this tool is to combine the concentrations of COC and its major metabolites with its breakdown pattern. For example, only 1–9% of a COC dose is excreted in urine unchanged, whilst 35–54% and 32–49% is excreted as BE and ecgonine methyl ester, respectively. Norbenzoylecgonine, norcocaine and coaethylene are minor metabolites and only account for traces of the urinary excretion pattern. In the back-calculations, a mean excretion rate of 45% for BE and of 10% for COC is taken into account, values in very good agreement with the distributions of BE/COC ratios of Fig. 2. The broad ranges for the excretion values of BE (15–55%) and COC (1–15%) can lead to uncertainties in the calculations. Table 2 summarises concentrations of BE and COC in various WWTPs, published the last 3 years. It can be seen that BE is coherently higher than COC with BE/COC ratios ranging from 0.9 to 5.0. However, 36.4% of the

samples exhibits a BE/COC ratio in the range of 3.1–3.5 and a further 18.2% between 3.6 and 4.0 (Fig. 2). According to Karolak et al. [50], BE/COC ratios lower than 5.0 suggest that COC has been discharged in WWTPs without being consumed, thus not metabolised to BE. The first formula, proposed by Zuccato et al. [57], was based on concentrations of BE, the major metabolite of COC, and which is present in wastewater at relatively high levels. From the concentrations of BE (ng/L) and the flow rate (L/day) of the wastewater stream, BE loads (g/day) can be calculated. These loads are then subsequently transformed into consumed COC (g/day) taking into account the molecular mass ratio of COC to BE (1.05) and the mid-range excretion percentage of 45% as BE [58]. This leads to the following equation:

$$\text{COC (g/day)} = \text{concentration BE (ng/L)} \times \text{flow rate (L/day)} \times 2.33$$

Fig. 2. Distribution of the BE/COC ratios in influents from WWTPs.

The result is the grams of COC used per day. Then, dividing the grams by the average dose (~100 mg [59]), we can have the number of doses per day and per number of equivalent inhabitants (by the in-flow rate of the WWTP). Most studies that report use of COC through wastewater analysis report consumption in the range of 31–2800 mg/day/1000 inhabitants [50,59–61]. Metcalfe et al. [52] also stated the use of other drugs through similar approaches and found that methamphetamine in Canada can be up to ~60 doses/day/1000 inhabitants.

IDs similarly to PPCPs are not efficiently removed during the wastewater treatment process. Karolak et al. [50] reported removal rates of COC ranging from 89.6 to 97.8% and BE removal rates from 69 to 93%, but MDMA removal rates were much lower and varied between 48.6 and 80.1%. Hummel et al. [62], Bones et al. [49] and Pedrouzo et al. [53] also reported that IDs are only partially removed through the sewage treatment and that further enhancements of the treatment technology are deemed necessary.

Fig. 3. Analysis strategy proposed by Katsoyiannis and Jones [64].

3.3. Prohibited doping substances

In 2010, Schroder et al. [21] published a study which for the first time presented concentrations of prohibited doping substances (steroids, β 2-agonists, stimulants, diuretic agents, and PDE V inhibitors) in the effluents of a sports centre, but also in large municipal WWTPs. Chemicals like testosterone, boldenone, ephedrine or stanozol were studied, and for some of these, the levels in the municipal WWTPs had reached values even in the levels of $\mu\text{g/L}$ (i.e. salbutamol's maximum concentration was $5.008 \mu\text{g/L}$).

Important implications from this study came from the view point by Katsoyiannis and Jones [63,64], according to which this kind of environmental analysis would be feasible during major athletic events (e.g. the Olympic Games). This way, anti-doping authorities could enhance their targeted testing and be more effective in identifying doped athletes. In light of this strategy, it should be possible to enhance targeted sampling to catch athletes using prohibited substances in main sport events through the analysis of wastewaters from all individual residences. It was suggested that the extensive number of collected samples should be used only as an "archive", leaving the routine analyses for the more centralised samples. Then, in cases of positive results, the archived samples should be analysed in order to backtrack where the breaching of regulations took place, as shown in Fig. 3. Furthermore, Katsoyiannis and Jones [64] suggested that epidemiology approaches similar to those for IDs should be applied to allow sports authorities to understand and tackle the consumption levels of doping substances. These compounds were found by Schroder et al. [21] to be removed at levels up to $\sim 100\%$ during conventional activated sludge treatment.

3.4. Persistent organic pollutants

Persistent organic pollutants (POPs), especially the legacy ones (polychlorinated biphenyls, polychlorinated dibenzo-*p*-dioxins/furans and organochlorine pesticides) have been studied in detail since the early 1980s [65–71]. It is widely known that legacy POPs in wastewaters originate from a variety of sources and, once in the WWTP, tend to partition mainly on the particulate phase and end up that way in the final sludge. Their fate is essentially governed by the physical–chemical properties, with K_{ow} playing the most important role [2,3,72–75]. The DOC has also been

shown to be of critical importance, enhancing the percent of POPs subject to advection, rather than sorption on particles [7,76]. For these compounds, modelling studies can be found in literature that have tried to estimate the final effluent, or sludge concentrations of POPs based on the respective influent concentrations [75,77,78], or works where the wastewater toxicity is correlated with POPs concentrations [79].

In the current study, the occurrence and fate of some of the newly introduced POPs to the Stockholm Convention is presented. In particular, flame retardants (FRs) (brominated and organophosphate, Table 3) and fluorinated organic chemicals (Table 4) are discussed.

As far as brominated FRs are concerned, polybrominated diphenyl ethers (PBDEs) are the most studied class and concentrations for Σ PBDEs in wastewaters can vary from few ng/L up to tens of $\mu\text{g/L}$ ($33 \mu\text{g/L}$ in influents from a WWTP in China [80]). In almost all studies, the range of Σ PBDE concentrations is too large, showing the impact that non-ordinary wastes can have on the load of WWTPs. PBDEs are hydrophobic compounds so they are expected to be removed mainly by sorption on particles and subsequent sedimentation. As can be seen in Table 3, in all studies reporting removal, the rates are higher than $\sim 70\%$ [80,81]. This results in very high concentrations of BDEs in sewage sludge. The profile and total BDE levels in wastewater or sludge depends highly on whether the deca-BDE (BDE-209) is analysed and taken into account or not. BDE-209 occurs in higher concentrations than the other BDEs, reflecting its widespread usage. As a matter of fact, in Europe, the deca-bromodiphenyl ether mixture (in which the main ingredient is BDE-209) accounted for 75% of the total usage. In a work by De la Torre et al. [82], a typical profile of PBDEs in sludges is characterised by BDE-209, which represents $77 \pm 11\%$ of the total BDE burden. Based on this and in the fact that BDE-209 comprised 75% of the European market, this result could be a strong evidence that under activated sludge treatment process, there is no substantial debromination of deca-BDE. This is further supported by the results of Peng et al. [80] and Fabrellas et al. (cited in Gevaio et al. [83]), where BDE-209 is up to 100 times higher than the sum of the other BDEs.

Daso et al. [84] reported that the occurrence of BDE-209 in influents of a WWTP in South Africa exhibits seasonality, with particularly low concentrations in warmer periods (April and June) than in cold ones. On the contrary, the levels of BDEs-47 and -99

Table 3
Flame retardants in WWTPs.

Compounds	Country	Influent (ng/L)	Effluent (ng/L)	Removal (%)	Sludge (ng/g dw)	References
PBDEs BB 153	South Africa	369 < Σ BDEs < 4370; BBE 153: mean 15.8	90.4 < Σ BDEs < 15,100; nd < BB 153 < 18.4	–	13.1 < Σ BDEs < 652; nd < BB 153 < 9.97	[84]
PBDEs	USA	Not specified	Σ BDEs: 0.004–29.1	–	Σ BDEs: 61–1440	[106]
PBDEs	Canada	Σ BDEs: 265 $\pm$ 210	Σ BDEs: 36 $\pm$ 10	BDEs: 86%	PS: 1626 $\pm$ 576; AS: 2698 $\pm$ 1141	[107]
PBDEs	China	3–7-BDEs: 1545–32,939 deca-BDE: 11.6–2412.6 Σ BDEs: 1557–35,350	3–7-BDEs: 0.267–0.689; 10-BDE: 0.6–3.4 Σ BDEs: 0.867–4.09	3–7-BDEs: >99%; 10-BDE: >70%	Tri-hepta BDEs: 8.5–96 Deca BDE: 150–22,894 Total BDEs: 158.5–23,856	[80]
PBDEs; BB 153	Australia	Σ BDEs: 70	Σ BDEs: 0.34	Σ BDEs: 99.5%	Σ BDEs: 220–460	[108]
PBDEs	Norway	Σ BDEs: nd-9.3	Σ BDEs nd-0.6	90–99%;	–	[109]
deBDethane, BDE 209	Sweden	deBDethane: 21.5 BDE-209: 200	deBDethane: 0.066; BDE 209: 0.405	deBDethane: 99.7%; BDE 209: 99.8%	deBDethane: 81; BDE 209: 800	[110]
PBDEs	USA	Σ BDEs: 4200–4300	Σ BDEs: 310–900	Σ BDEs: >78.6%	Σ BDEs: 1320–3800 ng/L	[111]
OPFRs	Sweden	--	Total FRs: <500–36,000	–	–	[112]
OPFRs	USA	Total FRs: 475–700	Total FRs: 450–700	Residual	Not applicable	[113]
OPFRs	Bosnia-Herzeg, Croatia, Serbia	TCEP: nd-500 TCPP: nd-2500	–	–	–	[114]
OPFRs	Germany	FRs: 81–4000	FRs: 20–3000	FRs: 0–89%	–	[115]
TCPP	Germany	240–1000 (520 $\pm$ 300)	230–610 (380 $\pm$ 170)	0–41%	TCPP: 5100	[87]
TCEP, TCPP	Austria, Belgium, Germany, Spain	FRs: 600	FRs: 200	66.7%	–	[116]
OPFRs	Sweden	Total FRs: 17,000–69,000	Total FRs: 7900–17,000	Total FRs: 23.5–79.7%	Total FRs: 620–6900	[86]
OPFRs	Germany	FRs: 180–61,000	FRs: 27–4700	FRs: 72.2–98.3%	–	[117]
BDEs, PBBs, TBPPA, 2,4,6-Tribromophenol	Sweden	–	–	–	Total BDEs nd-450 Individual BFRs: <0.3–390 TBPPA nd-220 2,4,6-Tribromophenol: nd-0.9 PBBs: nd	[118]
13 BDEs	China	–	Σ BDEs: 0.84	–	–	[119]
11 BDEs	Spain	–	–	–	BDEs: nd-1082 Σ BDEs: 197–1185	[120]
Tetra-, penta-, hexa-BDEs	UK	Σ BDEs: 180	–	–	–	[121]
13 BDEs, HBCD	Switzerland	–	–	–	BDEs: 0.2–617; HBCD: 39–597	[122]
PBDEs	Kuwait	–	–	–	Σ BDEs: 5.7–1599	[83]
PBDEs	Canada	–	–	–	BDEs: Raw: 20–650 PS: 10–320 Digested: 10–800	[123]
BDEs 47, 99, 153, 209	Holland	–	–	–	Σ BDEs: Influent: 31.5	[124]

Table 3 (Continued)

Compounds	Country	Influent (ng/L)	Effluent (ng/L)	Removal (%)	Sludge (ng/g dw)	References
PBDEs	Holland	BDEs: <0.02–330 ng/g ΣBDEs: <9.8–365 ng/g	BDEs: <0.3–920 ng/g ΣBDEs: 348–997 ng/g	–	Effluent: 372 BDEs: <0.4–330 ΣBDEs: 96–219	[124]
PBDEs	Germany	–	–	–	BDEs: 0.3–2217 ΣBDEs: 142–2491	[124]
20 BDEs	USA	–	–	–	BDEs: nd–58,800 ΣBDEs: 97,400	[125]
16 BDEs, OPFRs	USA	–	–	–	BDEs: nd–51,000 ΣBDEs: 185,000–627,000 Total FRs: 300,000–1,860,000	[126]
HBCD	Sweden	–	–	–	Primary sludge: 30–33 Digested sludge: nd	[127]
TBBPA	Canada	–	–	–	310 ± 90–330 ± 70	[128]
HBCD, TBBPA	Holland, UK, Ireland	HBCD: <0.4–3800 ng/g (dw); TBBPA: <3.9–21.7 ng/g (dw)	HBCD: <1–18 ng/g (dw); TBBPA: 3.1–63 ng/g (dw)	–	HBCD: <0.6–9120 TBBPA: 2–600	[129]
PBDEs	Italy	–	–	–	ΣPBDEs: 2763 (158–9427)	[130]

(the most important congeners of the penta-bromodiphenyl ether mixtures [85]) were much higher in the winter.

Table 3 also displays the occurrence of organophosphate FRs (OPFRs), which are less hydrophobic than PBDEs, having poor WS. They tend to occur in concentrations of hundreds to thousands of ng/L. In general, OPFRs are not efficiently removed during the wastewater treatment process. Marklund et al. [86] reported removal rates for individual OPFRs that ranged between –20% (tris-chloropropyl-phosphate, TCP) and 85% (tributylphosphate, TBP), whereas for the total OPFRs, the average elimination was 50%. Even lower removals were reported by Bester [87] (0–41% for TCP).

Chlorinated OPFRs are more stable against degradation processes than alkyl-, or aryl- OPFRs, and whether OPFRs will partition onto particles or remain in the water stream will be affected by the occurrence of DOC and other detergents, shifting the partition towards the aqueous phase [86].

3.5. Perfluorinated compounds

Contrarily to most BFRs, PFCs are not efficiently eliminated along a WWT process. In fact, in some cases it is often common to observe a phenomenon of negative removal or in-plant production [88]. Pan et al. [89] suggested the same fate when confronted with overall higher levels of PFCs in the effluents comparing to the influent flows. According to Heidler and Halden [88], several mass balances performed for fluorochemicals also reflect a net mass flow increase at the WWTP effluents. However, this family of compounds have dissimilar behaviour among them, depending on the functional groups [90]. For instance, some authors reported that perfluorooctanesulfonic acid or perfluorooctane sulfonate (PFOS) levels have a decreasing tendency after treatment in most WWTPs, whilst perfluorooctanoic acid or perfluorooctanoate (PFOA) showed an inverse pattern [89–91]. According to Guo et al. [90], this could be due to the higher organic carbon-normalised distribution coefficient of perfluoroalkylsulfonate (PFASs) in comparison with the carboxylate analog, a sign of preferential uptake of PFASs by the sludge, which seems to be a key mechanism in the process. Although Zhou et al. [92] state that, in terms of electrostatic interaction, PFOS and PFOA would suffer repulsion, making their adsorption impossible on activated sludge, they also consider that some cations present in the sludge (e.g. Ca^{2+} and Mg^{2+}) could provide the necessary ion bridges to allow the sorption of the negatively charged PFCs. Indeed, a review by Rayne and Forest [93] indicates that PFCs removal happens mainly through sorption on sludge. In a study to assess the sorption abilities of seven PFCs (heptafluorobutyric acid (PFBA), potassium perfluorobutanesulfonate (PFBS), undecafluorohexanoic acid (PFHxA), perfluorohexanesulfonic acid potassium salt (PFHxS), PFOA, PFOS, and perfluorododecanoic acid (PFDOA) on aerobic activated sludge, Zhou et al. [92] found out that the sorption of PFOS was highest when considering each compound individually. The same authors refer that the overall sorption capacities increased with the enlargement of the chain length for both the carboxylic and sulfonate compounds and, for the same number of carbons, were higher for the latter than for the former. Perfluorinated sulfonates possess one more tail carbon (longer CAF chain) than perfluorinated carboxylates, which enhances their hydrophobicity and reflects the significance of hydrophobic interaction in the sorption activity. Using a mixture of the seven PFCs, the same authors reported a significant decrease on the sorption capacities. For instance, PFOS sorption in the mixed solution was much higher than that of PFOA (as suggested by the respective isotherms), whose sorption decreased more than that of PFOS comparing to the single compound samples. The equilibrium of both compounds was obtained after about 11 h, enough time for them to be adsorbed on activated sludge on a WWTP normal process. Furthermore, their removal was lowered by the pH increase.

Table 4
PFCs in WWTPs.

Compounds	Country	Influent (ng/L)	Effluent (ng/L)	Removal (%)	Sludge (ng/g dw)	References
21 PFCs	Germany	–	PFCs: <0.004–82.2 ± 6.5; ΣPFCs: 30.5 ± 3.7–266.3 ± 17.2	–	–	[131]
9 PFCs	Japan	PFCs: <0.5–336; ΣPFCs: 56.7–449	PFCs: <0.1–635; ΣPFCs: 95.8–874.1	–	–	[97]
PFOS, PFOA	Japan	PFOS: 3.4–33 PFOA: 49–250	PFOS: 14–67 PFOA: 62–550	–	–	Nozoe et al. (2008), in [97]
PFHxS, PFOS, PFOA, PFNA, PFDA, PFUDA, 8:2 FTCA, 8:2 FTUCA	USA	PFCs: 0.12–8.9 g/day (1.8–117.0 ng/L); ΣPFCs: 4.6–15.5 g/day (68.2–203.7 ng/L)	PFCs: 0.13–21 g/day (1.9–276.0 ng/L); ΣPFCs: 8.0–43.7 g/day (118.7–574.2 ng/L); (6 WWTPs) PFCs: <2.5–398 ng/L; ΣPFCs: 86.5–1095.5 ng/L PFCs: <0.2–24.4; ΣPFCs: 6.3–39.9 PFCs: <0.16–1115; ΣPFCs: 17.8–1225.6	–	(5 PFCs) PFCs: <10–241; ΣPFCs: 88–530	[98]
PFOS, PFOSA, PFHxS, PFOA, PFNA, PFDA, PFUnA	Denmark	PFCs: <0.2–32.8; ΣPFCs: 11.3–76.6	–	–	PFCs: 0.4–74.1; ΣPFCs: 8.5–152.5	[100]
10 PFCs	Norway, Finland, Sweden, Denmark, Iceland, Faroe Islands	–	PFOS: 1.2–62.6; PFOSA: nd–0.48; ΣPFAS: 5–105.4	–	PFOS: 55–2644; PFOSA: nd–94	[132]
10 PFCs	USA	PFCs: <2–190 ΣPFCs: 90–470	PFCs: <2–85 Total PFCs: 100–170	–	ΣPFAS: 150–3793	[133]
PF ₈ A, PF ₁₀ A	Spain	–	PF ₈ A: <100–4300; PF ₁₀ A: 50–8170	–	–	[134]
PFOA, PFOS, PFBS, PFHxS, 6:2 FTS, PFHxA, PFNA, PFDA, FOSA	USA	PFCs: nd–400 ± 29; ΣPFCs: 60.4–509.2	PFCs: nd–370 ± 19 ΣPFCs: 3.6–569.5	–	–	[135]
15 PFCs	USA	PFCs: nd–33 ΣPFCs: 74.3	PFCs: nd–34 ΣPFCs: 70.9	PFOS: –53% PFDS: –30% PFOA: 27% PFNA: –209% FDA: 59%	PFCs: nd–160 ΣPFCs: 459.4	[91]
11 PFCs	Japan, Thailand	Individual PFCs: nd–908.3; ΣPFCs: 20–1862.4	PFCs: nd–1529.8; ΣPFCs: 21.5–3051.3	Not specified	PFCs: nd–1707.2; ΣPFCs: 187.4–4222.6 ng/L	[136]
PFOS, PFOA	Singapore	PFOS: 7.9 ± 1.9–374.5 ± 61.6; PFOA: 14.1 ± 4.0–638.2 ± 135.9	PFOS: 7.3 ± 2.2–461.7 ± 82.0; PFOA: 15.8 ± 2.8–1057.1 ± 205.8	Not specified	PFOS: 30.7 ± 6.8–702.2 ± 173.2; PFOA: 17.4 ± 5.4–69.0 ± 12.2	[137]
PFOS, PFOA	Singapore	–	PFOS: 5.8–532; PFOA: 7.9–1060	–	–	[138]

Table 4 (Continued)

Compounds	Country	Influent (ng/L)	Effluent (ng/L)	Removal (%)	Sludge (ng/g dw)	References
PFHxS, PFHpA, PFOA, PFOS, PFNA, PFDA, PFUnDA	China	ΣPFCs: 2.88–176	ΣPFCs: 5.48–498	Not specified	ΣPFCs: 1.21–326	[89]
PFOS, N-EtFOSE, N-EtFOAA, PFOSAA, N-EtFOA, FOSA, PFOSulfinate, PFOA	USA	PFCs: nd->400; ΣPFCs: >409.1	PFCs: nd-26±2.0; ΣPFCs: 51.6	Not specified	–	[95]
PFOA, PFNA, PFDA, PFUnA, PFOS	Canada	–	–	–	PFCs: nd-460; ΣPFCs: 47.4	[102]
[1,0]12 PFCs USA		–	–	–	PFCs: nd-2610; ΣPFCs: 5–3390	[139]
12 PFCs	Switzerland	–	–	–	PFCs: nd-750±20; ΣPFCs: 26–780	[140]
PFOS, PFOA	Germany	PFOS: <1–85; PFOA: 1.8–40	PFOS: <1–85; PFOA: 12–140	PFOS: 64% to –3000% PFOA: –25% to –511%	PFOS: 80–120 PFOA: 11–18	[141]
17 PFCs	Switzerland	–	–	–	PFCs: 1.1–670; ΣPFCs: 129–734	[142]
19 PFCs	China	PFCs: nd-49.9; ΣPFCs: 41.9–58.3	PFCs: nd-28.8; ΣPFCs: 25.8–31.4	PFBS: –36.4 and 53.6%; PFOS: 2.0 and 61.9%; PFHxA: –20% and 30%	PFCs: nd-157.9; ΣPFCs: 19.9–224.3	[143]
13 PFCs	USA	–	ΣPFCs: 62.3–418	–	–	[144]
10 PFCs	Thailand	PFCs: 0.1–465.4; ΣPFCs: 673.3–847.1	PFCs: nd-552.8; ΣPFCs: 661.8–1143.4	PFOA: –5.4 and –156%; PFOS: 59 and –54%	PFCs: nd-552.6; ΣPFCs: 1200.4–1534.5	[94]
PFOS, PFOA, PFBS, PFHxS, PFNA	Spain	–	PFCs: <0.03–72.1; ΣPFCs: 3.47–132	–	–	[145]
11 PFCs	Taiwan	PFCs: <0.1–348.3±66.2; ΣPFCs: 335.2–686.3	PFCs: <0.1–264.7±34; ΣPFCs: 379.2–481.4 PFCs: 2.8±0.3–5663.3±427.4; Mean ΣPFCs: 9456.5	PFOA: –7.6 and –9.6%; PFOS: 7 and –22.2%	–	[146]
PFHxA, PFHpA, PFOA, PFNA, PFDA, PFBS, PFHxS, PFOS	Australia	PFCs: nd-38.6±1; ΣPFCs: 24.2–137.7	–	–	–	[147]
13 PFCs	South Korea	PFCs: nd-615; Total PFCs: nd-628.6	PFCs: nd-591; ΣPFCs: nd-598.7	Not specified	PFCs: nd-54.1; ΣPFCs: nd-59.3	[90]
PFHxA, PFHpA, PFOA, PFNA, PFDA, PFUnA, PFDoA, PFHxS, PFOS	China	PFCs: nd-71.1; ΣPFCs: 71.8–120.5	PFCs: nd-41.1; ΣPFCs: 44.5–60.1	PFOA: –22 to 42%; PFOS: 41–70%	–	[148]
PFHxS, PFNA, PFOA, PFOS, PFOSA, PFDA, PFUnDA, PFDoDA	USA	PFCs: 0.17–184; ΣPFCs: 7.73–203.3	PFCs: <0.5–183; ΣPFCs: 12.2–205.9	PFOA: –577 to 0.5%; PFOS: –300 to 28%	PFCs: <2.5–993; ΣPFCs: 151–1616.5	[99]
18 PFCs	Greece	PFCs: <0.09–453.0 ΣPFCs: 12.6–856.3	PFCs: <0.09–209.4 ΣPFCs: 4.3–533.0	PFHxS: 73% PFOS: –408 to 64%	ΣPFCs: 151–1616.5 PFCs: <0.04–45.2 ΣPFCs: 0.58–233.3	[149]

Rayne and Forest [93] mentioned filtration and sorption methodologies as the most promising existing removal approaches for PFCs in wastewaters, together with the possibility of some sonochemical advances. Evaporative, extractive, thermal, advanced oxidative, direct and catalysed photochemical, reductive, and biodegradation techniques are yet short of validation for these systems. Slow kinetics impedes the direct use of most PFCs treatment methods in low residence time systems. In addition, the authors state that in concentrated solutions the polyfluorinated acid counterion is bound to influence the degradation and/or partitioning processes, but the extent of such influence is so far undetermined. In more dilute media (such as most wastewaters), the substrate reactivity and partitioning would potentially be independent of the input counterion.

On the other hand, Kunacheva et al. [94] found that two WWTPs with activated sludge processes failed to remove PFCs efficiently, which was a consequence of the non-biodegradability of those microcontaminants. Still, the authors agree that bio-accumulation in sludge could be the major removal mechanism of PFCs and that their increase in the effluents could be attributed to the existence and subsequent chemical and/or biological degradation of PFCs precursors such as perfluoroalkyl telomers or sulfonamides. This was confirmed by Boulanger et al. [95] and Schultz et al. [91].

Martin et al. [96] studied the importance of the precursors on the exposure of PFOS, whose concentrations in WWTPs exceed those of its precursors by one or more orders of magnitude. PFOSA, the most frequently analysed precursor, was often found below LODs. But even if they seldom appear in quantifiable limits, some studies advocate that precursors do play an important role in the levels of PFOS found in WWTP effluents and increases in its mass flow were found after activated sludge treatment in facilities from all over the world [97–100]. Rhoads et al. [101] found three potential precursors (perfluorooctanesulfonamide (PFOSA), methyl perfluorobutane sulfonamide (MeFBSA) and methyl perfluorobutane sulfonamidoethanol (MeFBSE)) in WWTPs and D'Eon et al. [102] stated the possibility of 4-carbon-chain (C4) compounds like MeFBSA and MeFBSE degrading into the C4 homologues of perfluoroalkyl carboxylates (PFCAs) and perfluoroalkyl sulfonates (PFSAs). Some researchers reported that laboratory experiments supported the field studies and concluded that aerobic microbial biodegradation of precursors can yield important loads of PFCs [101], but the actual understanding of these processes is still weak. In addition, it is also suggested that the percentage of industrial, commercial or domestic loads in the influents of WWTPs will affect the PFCs levels and profiles [98].

The physicochemical properties of fluorinated chemicals are not well known as for other microcontaminants (like PBCs for example). For PFOS, it is said that octanol/water partition coefficient cannot be calculated because PFOS forms multiple layers in octanol/water determination. According to US-EPA, PFOA, PFOS and other related microcontaminants have $\log K_{ow}$ that range between -1 and 7 . PFOS is almost totally water soluble and its pK_a is -3.3 . The latter value for PFOA is said to range between 2 and 3 [164–170].

Hence, the current knowledge on the behaviour of PFCs in WWTPs is influenced by all these intertwining and sometimes confounding factors, by the inexistence of a strong dataset reporting evidences on a significant number of facilities and treatment options and by a scarce experimental expertise on the physicochemical properties of almost all straight chain PFAs [93]. According to Heidler and Halden [88], future work to enhance the removal responses of WWTP systems should include an environmental impact assessment for chemicals accumulating in digested sludge and with high persistence throughout aerobic and anaerobic sewage treatment. Should degradation be limited or inexistent, more biodegradable and sustainable alternatives could ultimately prevent environmental and human health hazards.

4. Conclusions

The present review gave brief information about the occurrence of five categories of organic microcontaminants in WWTPs. PPCPs, IDs, doping substances, BFRs or PFCs are compounds that were probably present in wastewaters for decades. However, the scientific community only started dealing with them during the last years, either because the methodologies used in the past were not powerful enough to achieve low enough LODs, or simply because there was always the impression that these chemicals were easily biodegradable, making no sense to try to analyse them in WWTPs.

But since then, the analysis of these compounds has proved to have an outstanding impact and also important implications that go as far as the intersection between science and the society. For example, the epidemiological approach used to assess the consumption of cocaine in a city, based on the concentrations in WWTPs or the understanding of the use of doping substances, based on well designed sampling and analysis of effluents from Olympic villages.

Equally important is the recognition that many processes are yet poorly described and even unknown. This urges the continuous pursue of better analytical methodologies and optimised sampling strategies, in order to build an extensive dataset to help the enlightenment of such processes.

Acknowledgements

The Authors wish to thank the Guest Editors Dr. Stasinakis, Dr. Mamais and Dr. Thomaidis for their kind invitation to contribute to the present Special Issue, and the independent Reviewers who gave a number of great suggestions during the revision process.

Nuno Ratola wishes to thank Fundação para a Ciência e a Tecnologia (Portugal) for the scholarship SFRH/BPD/67088/2009.

References

- [1] E. Manoli, C. Samara, Occurrence and mass balance of polycyclic aromatic hydrocarbons in the Thessaloniki sewage treatment plant, *J. Environ. Qual.* 28 (1999) 176–187.
- [2] A. Katsoyiannis, C. Samara, Persistent organic pollutants (POPs) in the conventional activated sludge treatment process: fate and mass balance, *Environ. Res.* 97 (2005) 245–257.
- [3] A. Katsoyiannis, C. Samara, Persistent organic pollutants (POPs) in the sewage treatment plant of Thessaloniki, northern Greece: occurrence and removal, *Water Res.* 38 (2004) 2685–2698.
- [4] J.L. Stevens, G.L. Northcott, G.A. Stern, G.T. Tomy, K.C. Jones, PAHs, PCBs, PCNs, organochlorine pesticides, synthetic musks, and polychlorinated n-alkanes in UK sewage sludge: survey results and implications, *Environ. Sci. Technol.* 37 (2003) 462–467.
- [5] P.A. Bergqvist, L. Augulyte, V. Jurjonienė, PAH and PCB removal efficiencies in Umeå (Sweden) and Šiauliai (Lithuania) municipal wastewater treatment plants, *Water Air Soil Pollut.* 175 (2006) 291–303.
- [6] A. Katsoyiannis, C. Samara, Ecotoxicological evaluation of the wastewater treatment process of the sewage treatment plant of Thessaloniki, Greece, *J. Hazard. Mater.* 141 (2007) 614–621.
- [7] A. Katsoyiannis, C. Samara, The fate of dissolved organic carbon (DOC) in the wastewater treatment process and its importance in the removal of wastewater contaminants, *Environ. Sci. Pollut. Res.* 14 (2007) 284–292.
- [8] K. Ohlsen, T. Ternes, G. Werner, U. Wallner, D. Löffler, W. Ziebuhr, W. Witte, J. Hacker, Impact of antibiotics on conjugational resistance gene transfer in *Staphylococcus aureus* in sewage, *Environ. Microbiol.* 5 (2003) 711–716.
- [9] T. Ternes, M. Bonerz, T. Schmidt, Determination of neutral pharmaceuticals in wastewater and rivers by liquid chromatography–electrospray tandem mass spectrometry, *J. Chromatogr. A* 938 (2001) 175–185.
- [10] T. Ternes, Pharmaceuticals and metabolites as contaminants of the aquatic environment: an overview, *Abstr. Pap. Am. Chem. Soc.* 219 (2000) U622–U623.
- [11] R. Hirsch, T. Ternes, K. Haberer, K. Kratz, Occurrence of antibiotics in the aquatic environment, *Sci. Total Environ.* 225 (1999) 109–118.
- [12] A. Pistocchi, D. Marinov, S. Pontes, B.M. Gawlik, Continental scale inverse modeling of common organic water contaminants in European rivers, *Environ. Pollut.* 162 (2012) 159–167.
- [13] M.R. Boleda, M.T. Galceran, F. Ventura, Behavior of pharmaceuticals and drugs of abuse in a drinking water treatment plant (DWTP) using combined conventional and ultrafiltration and reverse osmosis (UF/RO) treatments, *Environ. Pollut.* 159 (2011) 1584–1591.

- [14] A. Jelic, M. Gros, A. Ginebreda, R. Cespedes-Sanchez, F. Ventura, M. Petrovic, D. Barcelo, Occurrence, partition and removal of pharmaceuticals in sewage water and sludge during wastewater treatment, *Water Res.* 45 (2011) 1165–1176.
- [15] C. Miege, J.M. Choubert, L. Ribeiro, M. Eusebe, M. Coquery, Fate of pharmaceuticals and personal care products in wastewater treatment plants – conception of a database and first results, *Environ. Pollut.* 157 (2009) 1721–1726.
- [16] J. Radjenovic, M. Petrovic, D. Barcelo, Fate and distribution of pharmaceuticals in wastewater and sewage sludge of the conventional activated sludge (CAS) and advanced membrane bioreactor (MBR) treatment, *Water Res.* 43 (2009) 831–841.
- [17] K.M. Onosios, J.T. Yu, E.J. Bouwer, Biodegradation and removal of pharmaceuticals and personal care products in treatment systems: a review, *Biodegradation* 20 (2009) 441–466.
- [18] S.K. Behera, H.W. Kim, J.E. Oh, H.S. Park, Occurrence and removal of antibiotics, hormones and several other pharmaceuticals in wastewater treatment plants of the largest industrial city of Korea, *Sci. Total Environ.* 409 (2011) 4351–4360.
- [19] V.G. Samaras, N.S. Thomaidis, A.S. Stasinakis, G. Gatidou, T.D. Lekkas, Determination of selected non-steroidal anti-inflammatory drugs in wastewater by gas chromatography–mass spectrometry, *Int. J. Environ. Anal. Chem.* 90 (2010) 219–229.
- [20] M. Petrovic, M.J.L. De Alda, S. Diaz-Cruz, C. Postigo, J. Radjenovic, M. Gros, D. Barcelo, Fate and removal of pharmaceuticals and illicit drugs in conventional and membrane bioreactor wastewater treatment plants and by riverbank filtration, *Philos. Trans. R. Soc. A* 367 (2009) 3979–4003.
- [21] H.F. Schroder, W. Gebhardt, M. Thevis, Anabolic, doping, and lifestyle drugs, and selected metabolites in wastewater-detection, quantification, and behaviour monitored by high-resolution MS and MS (n) before and after sewage treatment, *Anal. Bioanal. Chem.* 398 (2010) 1207–1229.
- [22] K.H. Langford, K.V. Thomas, Determination of pharmaceutical compounds in hospital effluents and their contribution to wastewater treatment works, *Environ. Int.* 35 (2009) 766–770.
- [23] W.J. Sim, J.W. Lee, E.S. Lee, S.K. Shin, S.R. Hwang, J.E. Oh, Occurrence and distribution of pharmaceuticals in wastewater from households, livestock farms, hospitals and pharmaceutical manufactures, *Chemosphere* 82 (2011) 179–186.
- [24] W.J. Sim, J.W. Lee, J.E. Oh, Occurrence and fate of pharmaceuticals in wastewater treatment plants and rivers in Korea, *Environ. Pollut.* 158 (2010) 1938–1947.
- [25] S. Terzic, I. Senta, M. Ahel, M. Gros, M. Petrovic, D. Barcelo, J. Muller, T. Knepper, I. Marti, F. Ventura, P. Jovancic, D. Jabucar, Occurrence and fate of emerging wastewater contaminants in Western Balkan Region, *Sci. Total Environ.* 399 (2008) 66–77.
- [26] N. Nakada, T. Tanishima, H. Shinohara, K. Kiri, H. Takada, Pharmaceutical chemicals and endocrine disruptors in municipal wastewater in Tokyo and their removal during activated sludge treatment, *Water Res.* 40 (2006) 3297–3303.
- [27] X. Yang, R.C. Flowers, H.S. Weinberg, P.C. Singer, Occurrence and removal of pharmaceuticals and personal care products (PPCPs) in an advanced wastewater reclamation plant, *Water Res.* 45 (2011) 5218–5228.
- [28] S. Zorita, L. Martensson, L. Mathiasson, Occurrence and removal of pharmaceuticals in a municipal sewage treatment system in the south of Sweden, *Sci. Total Environ.* 407 (2009) 2760–2770.
- [29] A.Y.-C. Lin, C.-F. Lin, J.-M. Chiou, P.K.A. Hong, O(3) and O(3)/H(2)O(2) treatment of sulfonamide and macrolide antibiotics in wastewater, *J. Hazard. Mater.* 171 (2009) 452–458.
- [30] T.-H. Yu, A.Y.-C. Lin, S.K. Lateef, C.-F. Lin, P.-Y. Yang, Removal of antibiotics and non-steroidal anti-inflammatory drugs by extended sludge age biological process, *Chemosphere* 77 (2009) 175–181.
- [31] R. Molinari, F. Pirillo, V. Loddò, L. Palmisano, Heterogeneous photocatalytic degradation of pharmaceuticals in water by using polycrystalline TiO₂ and a nanofiltration membrane reactor, *Catal. Today* 118 (2006) 205–213.
- [32] B. De Witte, H. Van Langenhove, K. Hemelsoet, K. Demeestere, P. De Wispelaere, V. Van Speybroeck, J. Dewulf, Levofloxacin ozonation in water: rate determining process parameters and reaction pathway elucidation, *Chemosphere* 76 (2009) 683–689.
- [33] T.E. Doll, F.H. Frimmel, Fate of pharmaceuticals–photodegradation by simulated solar UV-light, *Chemosphere* 52 (2003) 1757–1769.
- [34] T.E. Doll, F.H. Frimmel, Removal of selected persistent organic pollutants by heterogeneous photocatalysis in water, *Catal. Today* 101 (2005) 195–202.
- [35] D. Vogna, R. Marotta, A. Napolitano, R. Andreozzi, M. d'Ischia, Advanced oxidation of the pharmaceutical drug diclofenac with UV/H₂O₂ and ozone, *Water Res.* 38 (2004) 414–422.
- [36] R. Andreozzi, V. Caprio, R. Marotta, A. Radonkovic, Ozonation and H₂O₂/UV treatment of clofibric acid in water: a kinetic investigation, *J. Hazard. Mater.* 103 (2003) 233–246.
- [37] Y.P. Zhang, J.L. Zhou, Removal of estrone and 17 beta-estradiol from water by adsorption, *Water Res.* 39 (2005) 3991–4003.
- [38] M.G. Maniero, D.M. Bila, M. Dezotti, Degradation estrogenic activity removal of 17 beta-estradiol and 17 alpha-ethinylestradiol by ozonation and O(3)/H(2)O(2), *Sci. Total Environ.* 407 (2008) 105–115.
- [39] I. Senta, M. Matosic, H.K. Jakopovic, S. Terzic, J. Curko, I. Mijatovic, M. Ahel, Removal of antimicrobials using advanced wastewater treatment, *J. Hazard. Mater.* 192 (2011) 319–328.
- [40] M.S. Diaz-Cruz, M.J. Garcia-Galan, P. Guerra, A. Jelic, C. Postigo, E. Eljarrat, M. Farre, M.J.L. de Alda, M. Petrovic, D. Barcelo, Analysis of selected emerging contaminants in sewage sludge, *TrAC-Trends Anal. Chem.* 28 (2009) 1263–1275.
- [41] J. Radjenovic, A. Jelic, M. Petrovic, D. Barcelo, Determination of pharmaceuticals in sewage sludge by pressurized liquid extraction (PLE) coupled to liquid chromatography–tandem mass spectrometry (LC–MS/MS), *Anal. Bioanal. Chem.* 393 (2009) 1685–1695.
- [42] V.G. Samaras, N.S. Thomaidis, A.S. Stasinakis, T.D. Lekkas, An analytical method for the simultaneous trace determination of acidic pharmaceuticals and phenolic endocrine disrupting chemicals in wastewater and sewage sludge by gas chromatography–mass spectrometry, *Anal. Bioanal. Chem.* 399 (2011) 2549–2561.
- [43] M. Horsing, A. Ledin, R. Grabic, J. Fick, M. Tysklind, J.I.C. Jansen, H.R. Andersen, Determination of sorption of seventy-five pharmaceuticals in sewage sludge, *Water Res.* 45 (2011) 4470–4482.
- [44] A.S. Stasinakis, C.I. Kordoutis, V.C. Tsiouma, G. Gatidou, N.S. Thomaidis, Removal of selected endocrine disruptors in activated sludge systems: effect of sludge retention time on their sorption and biodegradation, *Bioresour. Technol.* 101 (2010) 2090–2095.
- [45] A.S. Stasinakis, A.V. Petalas, D. Mamais, N.S. Thomaidis, G. Gatidou, T.D. Lekkas, Investigation of triclosan fate and toxicity in continuous-flow activated sludge systems, *Chemosphere* 68 (2007) 375–381.
- [46] D.R. Baker, B. Kasprzyk-Hordern, Multi-residue analysis of drugs of abuse in wastewater and surface water by solid-phase extraction and liquid chromatography–positive electrospray ionisation tandem mass spectrometry, *J. Chromatogr. A* 1218 (2011) 1620–1631.
- [47] E. Zuccato, S. Castiglioni, R. Bagnati, M. Melis, R. Fanelli, Source, occurrence and fate of antibiotics in the Italian aquatic environment, *J. Hazard. Mater.* 179 (2010) 1042–1048.
- [48] A.L.N. van Nuijs, S. Castiglioni, I. Tarcomnicu, C. Postigo, M.L. de Alda, H. Neels, E. Zuccato, D. Barcelo, A. Covaci, Illicit drug consumption estimations derived from wastewater analysis: a critical review, *Sci. Total Environ.* 409 (2011) 3564–3577.
- [49] J. Bones, K.V. Thomas, B. Paull, Using Environ analytical data to estimate levels of community consumption of illicit drugs and abused pharmaceuticals, *J. Environ. Monit.* 9 (2007) 701–707.
- [50] S. Karolak, T. Nefau, E. Bailly, A. Solgadi, Y. Levi, Estimation of illicit drugs consumption by wastewater analysis in Paris area (France), *Forensic Sci. Int.* 200 (2010) 153–160.
- [51] M. Huerta-Fontela, M.T. Galceran, F. Ventura, Ultraperformance liquid chromatography–tandem mass spectrometry analysis of stimulatory drugs of abuse in wastewater and surface waters, *Anal. Chem.* 79 (2007) 3821–3829.
- [52] C. Metcalfe, K. Tindale, H. Li, A. Rodayan, V. Yargeau, Illicit drugs in Canadian municipal wastewater and estimates of community drug use, *Environ. Pollut.* 158 (2010) 3179–3185.
- [53] M. Pedrouzo, F. Borrull, E. Pocurull, R. Maria Marce, Drugs of abuse and their metabolites in waste and surface waters by liquid chromatography–tandem mass spectrometry, *J. Sep. Sci.* 34 (2011) 1091–1101.
- [54] S. Castiglioni, R. Bagnati, M. Melis, D. Panawennage, P. Chiarelli, R. Fanelli, E. Zuccato, Identification of cocaine and its metabolites in urban wastewater and comparison with the human excretion profile in urine, *Water Res.* 45 (2011) 5141–5150.
- [55] J.D. Berset, R. Brenneisen, C. Mathieu, Analysis of illicit and illicit drugs in waste, surface and lake water samples using large volume direct injection high performance liquid chromatography–electrospray tandem mass spectrometry (HPLC–MS/MS), *Chemosphere* 81 (2010) 859–866.
- [56] E. Zuccato, S. Castiglioni, M. Tettamanti, R. Olandese, R. Bagnati, M. Melis, R. Fanelli, Changes in illicit drug consumption patterns in 2009 detected by wastewater analysis, *Drug Alcohol Depend.* 118 (2011) 464–469.
- [57] E. Zuccato, C. Chiabrando, S. Castiglioni, D. Calamari, R. Bagnati, S. Schiarea, R. Fanelli, Cocaine in surface waters: a new evidence-based tool to monitor community drug abuse, *Environ. Health* 4 (2005) 14.
- [58] R.C. Baselt, Disposition of Toxic Drugs and Chemicals in Man, 8th ed., Biomedical Publications, Foster City, California, USA, 2008.
- [59] A.L.N. van Nuijs, J.-F. Mougel, I. Tarcomnicu, L. Bervoets, R. Blust, P.G. Jorens, H. Neels, A. Covaci, Sewage epidemiology – a real-time approach to estimate the consumption of illicit drugs in Brussels, Belgium, *Environ. Int.* 37 (2011) 612–621.
- [60] C. Harman, M. Reid, K.V. Thomas, In situ calibration of a passive sampling device for selected illicit drugs and their metabolites in wastewater, and subsequent year-long assessment of community drug usage, *Environ. Sci. Technol.* 45 (2011) 5676–5682.
- [61] D. Gerrity, R.A. Trenholm, S.A. Snyder, Temporal variability of pharmaceuticals and illicit drugs in wastewater and the effects of a major sporting event, *Water Res.* 45 (2011) 5399–5411.
- [62] D. Hummel, D. Loeffler, G. Fink, T.A. Ternes, Simultaneous determination of psychoactive drugs and their metabolites in aqueous matrices by liquid chromatography mass spectrometry, *Environ. Sci. Technol.* 40 (2006) 7321–7328.
- [63] A. Katsoyiannis, K. Jones, Response to the letter to the editor concerning the viewpoint an anti-doping sampling Strategy utilizing the sewerage systems of sport villages, *Environ. Sci. Technol.* 45 (2011) 4192.
- [64] A. Katsoyiannis, K.C. Jones, An anti-doping sampling strategy utilizing the sewerage systems of sport villages, *Environ. Sci. Technol.* 45 (2011) 362–363.
- [65] M. Chevreuil, L. Granier, A. Chesterikoff, R. Letolle, Polychlorinated biphenyls partitioning in waters from river, filtration plant and wastewater plant: the case for Paris (France), *Water Res.* 24 (1990) 1325–1333.

- [66] T.T. Pham, S. Proulx, PCBs and PAHs in the Montreal urban community (Quebec, Canada) wastewater treatment plant and in the effluent plume in the St. Lawrence river, *Water Res.* 31 (1997) 1887–1896.
- [67] M. Blanchard, M.J. Teil, D. Ollivon, B. Garban, C. Chestérikoff, M. Chevreuil, Origin and distribution of polyaromatic hydrocarbons and polychlorobiphenyls in urban effluents to wastewater treatment plants of the Paris area (FRANCE), *Water Res.* 35 (2001) 3679–3687.
- [68] A.B. Van Luin, W. Van Starkenburg, Hazardous substances in waste water, *Water Sci. Technol.* 17 (1985) 843–853.
- [69] L.F. De Alencastro, J. Tarradellas, Concentration of polychlorinated biphenyls in sewage, Etude de la concentration en PCBs des eaux usées dans les stations d'épuration 63 (1983) 113–122.
- [70] M. Blanchard, M.J. Teil, D. Ollivon, L. Legenti, M. Chevreuil, Polycyclic aromatic hydrocarbons and polychlorobiphenyls in wastewaters and sewage sludges from the Paris area (France), *Environ. Res.* 95 (2004) 184–197.
- [71] S. Morris, J.N. Lester, Behaviour and fate of polychlorinated biphenyls in a pilot wastewater treatment plant, *Water Res.* 28 (1994) 1553–1561.
- [72] Q.Y. Cai, C.H. Mo, Q.T. Wu, Q.Y. Zeng, A. Katsoyiannis, J.F. Ferard, Bioremediation of polycyclic aromatic hydrocarbons (PAHs)-contaminated sewage sludge by different composting processes, *J. Hazard. Mater.* 142 (2007) 535–542.
- [73] A. Katsoyiannis, E. Terzi, Q.Y. Cai, On the use of PAH molecular diagnostic ratios in sewage sludge for the understanding of the PAH sources. Is this use appropriate? *Chemosphere* 69 (2007) 1337–1339.
- [74] Q.Y. Cai, C.H. Mo, Q.T. Wu, Q.Y. Zeng, A. Katsoyiannis, Occurrence of organic contaminants in sewage sludges from eleven wastewater treatment plants, China, *Chemosphere* 68 (2007) 1751–1762.
- [75] A. Katsoyiannis, A. Zouboulis, C. Samara, Persistent organic pollutants (POPs) in the conventional activated sludge treatment process: model predictions against experimental values, *Chemosphere* 65 (2006) 1634–1641.
- [76] P.A. Neale, A. Antony, W. Gernjak, G. Leslie, B.I. Escher, Natural versus wastewater derived dissolved organic carbon: implications for the Environ fate of organic micropollutants, *Water Res.* 45 (2011) 4227–4237.
- [77] M.W. Sweeney, J.C. Kabouris, Modeling, instrumentation, automation, and optimization of wastewater treatment facilities, *Water Environ. Res.* 79 (2007) 1551–1567.
- [78] G. Byrns, The fate of xenobiotic organic compounds in wastewater treatment plants, *Water Res.* 35 (2001) 2523–2533.
- [79] I. Mantis, D. Voutsas, C. Samara, Assessment of the Environ hazard from municipal and industrial wastewater treatment sludge by employing chemical and biological methods, *Ecotoxicol. Environ. Saf.* 62 (2005) 397–407.
- [80] X. Peng, C. Tang, Y. Yu, J. Tan, Q. Huang, J. Wu, S. Chen, B. Mai, Concentrations, transport, fate, and releases of polybrominated diphenyl ethers in sewage treatment plants in the Pearl River Delta, South China, *Environ. Int.* 35 (2009) 303–309.
- [81] M. Song, S.G. Chu, R.J. Letcher, R. Seth, Fate, partitioning, and mass loading of polybrominated diphenyl ethers (PBDEs) during the treatment processing of municipal sewage, *Environ. Sci. Technol.* 40 (2006) 6241–6246.
- [82] A. De la Torre, E. Alonso, M.A. Concejero, P. Sanz, M.A. Martínez, Sources and behaviour of polybrominated diphenyl ethers (PBDEs), polychlorinated dibenzo-p-dioxins and dibenzofurans (PCDD/Fs) in Spanish sewage sludge, *Waste Manag.* 31 (2011) 1277–1284.
- [83] B. Gevaio, S. Muzaini, M. Helaleh, Occurrence and concentrations of polybrominated diphenyl ethers in sewage sludge from three wastewater treatment plants in Kuwait, *Chemosphere* 71 (2008) 242–247.
- [84] A. Daso, O. Fatoki, J. Odendaal, O. Olujimi, Occurrence of selected polybrominated diphenyl ethers and 2,2',4,4',5,5'-hexabromobiphenyl (BB-153) in sewage sludge and effluent samples of a wastewater-treatment plant in Cape Town, South Africa, *Arch. Environ. Contam. Toxicol.* (2012) 391–402.
- [85] M.J. La Guardia, R.C. Hale, E. Harvey, Detailed polybrominated diphenyl ether (PBDE) congener composition of the widely used penta-, octa-, and deca-PBDE technical flame-retardant mixtures, *Environ. Sci. Technol.* 40 (2006) 6247–6254.
- [86] A. Marklund, B. Andersson, P. Haglund, Organophosphorus flame retardants and plasticizers in Swedish sewage treatment plants, *Environ. Sci. Technol.* 39 (2005) 7423–7429.
- [87] K. Bester, Comparison of TCP concentrations in sludge and wastewater in a typical German sewage treatment plant – comparison of sewage sludge from 20 plants, *J. Environ. Monit.* 7 (2005) 509–513.
- [88] J. Heidler, R.U. Halden, Meta-analysis of mass balances examining chemical fate during wastewater treatment, *Environ. Sci. Technol.* 42 (2008) 6324–6332.
- [89] Y. Pan, Y. Shi, J. Wang, Y. Cai, Evaluation of perfluorinated compounds in seven wastewater treatment plants in Beijing urban areas, *Sci. China Chem.* 54 (2011) 552–558.
- [90] R. Guo, W.J. Sim, E.S. Lee, J.H. Lee, J.E. Oh, Evaluation of the fate of perfluoroalkyl compounds in wastewater treatment plants, *Water Res.* 44 (2010) 3476–3486.
- [91] M.M. Schultz, C.P. Higgins, C.A. Huset, R.G. Luthy, D.F. Barofsky, J.A. Field, Fluorochemical mass flows in a municipal wastewater treatment facility, *Environ. Sci. Technol.* 40 (2006) 7350–7357.
- [92] Q. Zhou, S. Deng, Q. Zhang, Q. Fan, J. Huang, G. Yu, Sorption of perfluorooctane sulfonate and perfluorooctanoate on activated sludge, *Chemosphere* 81 (2010) 453–458.
- [93] S. Rayne, K. Forest, Perfluoroalkyl sulfonic and carboxylic acids: a critical review of physicochemical properties, levels and patterns in waters and wastewaters, and treatment methods, *J. Environ. Sci. Health Part A* 44 (2009) 1145–1199.
- [94] C. Kunacheva, S. Tanaka, S. Fujii, S.K. Boontanon, C. Musirat, T. Wongwatana, B.R. Shivakoti, Mass flows of perfluorinated compounds (PFCs) in central wastewater treatment plants of industrial zones in Thailand, *Chemosphere* 83 (2011) 737–744.
- [95] B. Boulanger, J.D. Vargo, J.L. Schnoor, K.C. Hornbuckle, Evaluation of perfluorooctane surfactants in a wastewater treatment system and in a commercial surface protection product, *Environ. Sci. Technol.* 39 (2005) 5524–5530.
- [96] J.W. Martin, B.J. Asher, S. Beesoon, J.P. Benskin, M.S. Ross, PFOS or PreFOS? Are perfluorooctane sulfonate precursors (PreFOS) important determinants of human and Environ perfluorooctane sulfonate (PFOS) exposure? *J. Environ. Monit.* 12 (2010) 1979–2004.
- [97] M. Murakami, H. Shinohara, H. Takada, Evaluation of wastewater and street runoff as sources of perfluorinated surfactants (PFSS), *Chemosphere* 74 (2009) 487–493.
- [98] E. Sinclair, K. Kannan, Mass loading and fate of perfluoroalkyl surfactants in wastewater treatment plants, *Environ. Sci. Technol.* 40 (2006) 1408–1414.
- [99] B.G. Loganathan, K.S. Sajwan, E. Sinclair, S. Senthil Kumar, K. Kannan, Perfluoroalkyl sulfonates and perfluorocarboxylates in two wastewater treatment facilities in Kentucky and Georgia, *Water Res.* 41 (2007) 4611–4620.
- [100] R. Bossi, J. Strand, O. Sortkjær, M.M. Larsen, Perfluoroalkyl compounds in Danish wastewater treatment plants and aquatic environments, *Environ. Int.* 34 (2008) 443–450.
- [101] K.R. Rhoads, E.M.L. Janssen, R.G. Luthy, C.S. Criddle, Aerobic biotransformation and fate of N-ethyl perfluorooctane sulfonamidoethanol (N-ETFOSE) in activated sludge, *Environ. Sci. Technol.* 42 (2008) 2873–2878.
- [102] J.C. D'Eon, P.W. Crozier, V.I. Furdul, E.J. Reiner, E. Laurence Libelo, S.A. Mabury, Observation of a commercial fluorinated material, the polyfluoroalkyl phosphoric acid diesters, in human sera, wastewater treatment plant sludge, and paper fibers, *Environ. Sci. Technol.* 43 (2009) 4589–4594.
- [103] C. Mathieu, J. Rieckermann, J.D. Berset, S. Schurch, R. Brenneisen, Assessment of total uncertainty in cocaine and benzoylecgonine wastewater load measurements, *Water Res.* 45 (2011) 6650–6660.
- [104] K.J. Bisceglia, A.L. Roberts, K.A. Lippa, A hydrolysis procedure for the analysis of total cocaine residues in wastewater, *Anal. Bioanal. Chem.* 402 (2012) 1277–1287.
- [105] C. Postigo, M.L. de Alda, D. Barcelo, Evaluation of drugs of abuse use and trends in a prison through wastewater analysis, *Environ. Int.* 37 (2011) 49–55.
- [106] K.D. North, Tracking polybrominated diphenyl ether releases in a wastewater treatment plant effluent, Palo Alto, California, *Environ. Sci. Technol.* 38 (2004) 4484–4488.
- [107] M. Song, S. Chu, R.J. Letcher, R. Seth, Fate, partitioning, and mass loading of polybrominated diphenyl ethers (PBDEs) during the treatment processing of municipal sewage, *Environ. Sci. Technol.* 40 (2006) 6241–6246.
- [108] B.O. Clarke, N.A. Porter, R.K. Symons, P.J. Marriott, G.J. Stevenson, J.R. Blackbeard, Investigating the distribution of polybrominated diphenyl ethers through an Australian wastewater treatment plant, *Sci. Total Environ.* 408 (2010) 1604–1611.
- [109] C. Vogelsang, M. Grung, T.G. Jantsch, K.E. Tollefsen, H. Liltved, Occurrence and removal of selected organic micropollutants at mechanical, chemical and advanced wastewater treatment plants in Norway, *Water Res.* 40 (2006) 3559–3570.
- [110] N. Ricklund, A. Kierkegaard, M.S. McLachlan, C. Wahlberg, Mass balance of decabromodiphenyl ethane and decabromodiphenyl ether in a WWTP, *Chemosphere* 74 (2009) 389–394.
- [111] T.D. Anderson, J.D. MacRae, Polybrominated diphenyl ethers in fish and wastewater samples from an area of the Penobscot River in Central Maine, *Chemosphere* 62 (2006) 1153–1160.
- [112] N. Paxeus, Organic pollutants in the effluents of large wastewater treatment plants in Sweden, *Water Res.* 30 (1996) 1115–1122.
- [113] P.E. Stackelberg, E.T. Furlong, M.T. Meyer, S.D. Zaugg, A.K. Henderson, D.B. Reissman, Persistence of pharmaceutical compounds and other organic wastewater contaminants in a conventional drinking-water treatment plant, *Sci. Total Environ.* 329 (2004) 99–113.
- [114] S. Terzic, I. Senta, M. Ahel, M. Gros, M. Petrovic, D. Barcelo, J. Mueller, T. Knepper, I. Marti, F. Ventura, P. Jovancic, D. Jabucar, Occurrence and fate of emerging wastewater contaminants in Western Balkan Region, *Sci. Total Environ.* 399 (2008) 66–77.
- [115] J. Meyer, K. Bester, Organophosphate flame retardants and plasticisers in wastewater treatment plants, *J. Environ. Monit.* 6 (2004) 599–605.
- [116] T. Reemtsma, S. Weiss, J. Mueller, M. Petrovic, S. Gonzalez, D. Barcelo, F. Ventura, T.P. Knepper, Polar pollutants entry into the water cycle by municipal wastewater: a European perspective, *Environ. Sci. Technol.* 40 (2006) 5451–5458.
- [117] J.B. Quintana, R. Rodil, T. Reemtsma, Determination of phosphoric acid mono- and diesters in municipal wastewater by solid-phase extraction and ion-pair liquid chromatography–tandem mass spectrometry, *Anal. Chem.* 78 (2006) 1644–1650.
- [118] K. Oberg, K. Warman, T. Oberg, Distribution and levels of brominated flame retardants in sewage sludge, *Chemosphere* 48 (2002) 805–809.
- [119] Y. Wang, X. Li, A. Li, T. Wang, Q. Zhang, P. Wang, J. Fu, G. Jiang, Effect of municipal sewage treatment plant effluent on bioaccumulation of polychlorinated biphenyls and polybrominated diphenyl ethers in the recipient water, *Environ. Sci. Technol.* 41 (2007) 6026–6032.

- [120] E. Eljarrat, G. Marsh, A. Labandeira, D. Barcelo, Effect of sewage sludges contaminated with polybrominated diphenylethers on agricultural soils, *Chemosphere* 71 (2008) 1079–1086.
- [121] K.L. Rule, S.D.W. Comber, D. Ross, A. Thornton, C.K. Makropoulos, R. Rautiu, Sources of priority substances entering an urban wastewater catchment – trace organic chemicals, *Chemosphere* 63 (2006) 581–591.
- [122] T. Kupper, L.F. de Alencastro, R. Gatsigazi, R. Furrer, D. Grandjean, J. Taradellas, Concentrations and specific loads of brominated flame retardants in sewage sludge, *Chemosphere* 71 (2008) 1173–1180.
- [123] M. Shin, M.L. Svoboda, P. Falletta, Microwave-assisted extraction (MAE) for the determination of polybrominated diphenylethers (PBDEs) in sewage sludge, *Anal. Bioanal. Chem.* 387 (2007) 2923–2929.
- [124] J. De Boer, P.G. Wester, A. Van Der Horst, P.E.G. Leonards, Polybrominated diphenyl ethers in influents, suspended particulate matter, sediments, sewage treatment plant and effluents and biota from the Netherlands, *Environ. Pollut.* 122 (2003) 63–74.
- [125] M.J. La Guardia, R.C. Hale, E. Harvey, Evidence of debromination of decabromodiphenyl ether (BDE-209) in biota from a wastewater receiving stream, *Environ. Sci. Technol.* 41 (2007) 6663–6670.
- [126] M.J.L. Guardia, R.C. Hale, E. Harvey, D. Chen, Flame-retardants and other organohalogens detected in sewage sludge by electron capture negative ion mass spectrometry, *Environ. Sci. Technol.* 44 (2010) 4658–4664.
- [127] M. Remberger, J. Sternbeck, A. Palm, L. Kaj, K. Strömberg, E. Brorström-Lundén, The Environ occurrence of hexabromocyclododecane in Sweden, *Chemosphere* 54 (2004) 9–21.
- [128] R. Saint-Louis, E. Pelletier, LC-ESI-MS-MS method for the analysis of tetrabromobisphenol A in sediment and sewage sludge, *Analyst* 129 (2004) 724–730.
- [129] S. Morris, C.R. Allchin, B.N. Zegers, J.J.H. Hafka, J.P. Boon, C. Belpaire, P.E.G. Leonards, S.P.J. Van Leeuwen, J. De Boer, Distribution and fate of HBCD and TBPA brominated flame retardants in North Sea estuaries and aquatic food webs, *Environ. Sci. Technol.* 38 (2004) 5497–5504.
- [130] A. Cincinelli, T. Martellini, L. Misuri, E. Lanciotti, A. Sweetman, S. Laschi, I. Palchetti, PBDEs in Italian sewage sludge and Environ risk of using sewage sludge for land application, *Environ. Pollut.* 161 (2012) 229–234.
- [131] L. Ahrens, S. Felizeter, R. Sturm, Z. Xie, R. Ebinghaus, Polyfluorinated compounds in waste water treatment plant effluents and surface waters along the River Elbe, Germany, *Mar. Pollut. Bull.* 58 (2009) 1326–1333.
- [132] R. Kallenborn, U. Berger, U. Järnberg, Perfluorinated Alkylated Substances (PFAS) in the Nordic Environment, Nordic Council of Ministers, Tema Nord. Copenhagen, Denmark, 2004, p. 552.
- [133] M.H. Plumlee, J. Larabee, M. Reinhard, Perfluorochemicals in water reuse, *Chemosphere* 72 (2008) 1541–1547.
- [134] R. Alzaga, J.M. Bayona, Determination of perfluorocarboxylic acids in aqueous matrices by ion-pair solid-phase microextraction-in-port derivatization-gas chromatography-negative ion chemical ionization mass spectrometry, *J. Chromatogr. A* 1042 (2004) 155–162.
- [135] M.M. Schultz, D.F. Barofsky, J.A. Field, Quantitative determination of fluorinated alkyl substances by large-volume-injection liquid chromatography tandem mass spectrometry – characterization of municipal wastewaters, *Environ. Sci. Technol.* 40 (2006) 289–295.
- [136] B.R. Shivakoti, S. Tanaka, S. Fujii, K. Kunacheva, S.K. Boontanon, C. Musirat, S.T.M.L.D. Seneviratne, H. Tanaka, Occurrences and behavior of perfluorinated compounds (PFCs) in several wastewater treatment plants (WWTPs) in Japan and Thailand, *J. Environ. Monit.* 12 (2010) 1255–1264.
- [137] J. Yu, J. Hu, S. Tanaka, S. Fujii, Perfluorooctane sulfonate (PFOS) and perfluorooctanoic acid (PFOA) in sewage treatment plants, *Water Res.* 43 (2009) 2399–2408.
- [138] J. Hu, J. Yu, S. Tanaka, S. Fujii, Perfluorooctane sulfonate (PFOS) and perfluorooctanoic acid (PFOA) in water environment of Singapore, *Water Air Soil Pollut.* 216 (2011) 179–191.
- [139] C.P. Higgins, J.A. Field, C.S. Cridle, R.G. Luthy, Quantitative determination of perfluorochemicals in sediments and domestic sludge, *Environ. Sci. Technol.* 39 (2005) 3946–3956.
- [140] H. Sun, A.C. Gerecke, W. Giger, A.C. Alder, Long-chain perfluorinated chemicals in digested sewage sludges in Switzerland, *Environ. Pollut.* 159 (2011) 654–662.
- [141] A.M. Becker, S. Gerstmann, H. Frank, Perfluorooctane surfactants in waste waters, the major source of river pollution, *Chemosphere* 72 (2008) 115–121.
- [142] T. Zhang, H. Sun, A.C. Gerecke, K. Kannan, C.E. Müller, A.C. Alder, Comparison of two extraction methods for the analysis of per- and polyfluorinated chemicals in digested sewage sludge, *J. Chromatogr. A* 1217 (2010) 5026–5034.
- [143] R. Ma, K. Shih, Perfluorochemicals in wastewater treatment plants and sediments in Hong Kong, *Environ. Pollut.* 158 (2010) 1354–1362.
- [144] C.V. Furl, C.A. Meredith, M.J. Strynar, S.F. Nakayama, Relative importance of wastewater treatment plants and non-point sources of perfluorinated compounds to Washington State rivers, *Sci. Total Environ.* 409 (2011) 2902–2907.
- [145] J. Sánchez-Avila, J. Meyer, S. Lacorte, Spatial distribution and sources of perfluorochemicals in the NW Mediterranean coastal waters (Catalonia, Spain), *Environ. Pollut.* 158 (2010) 2833–2840.
- [146] A.Y.C. Lin, S.C. Panchangam, P.S. Ciou, High levels of perfluorochemicals in Taiwan's wastewater treatment plants and downstream rivers pose great risk to local aquatic ecosystems, *Chemosphere* 80 (2010) 1167–1174.
- [147] J. Thompson, G. Eaglesham, J. Reungoat, Y. Poussade, M. Bartkow, M. Lawrence, J.F. Mueller, Removal of PFOS, PFOA and other perfluoroalkyl acids at water reclamation plants in South East Queensland Australia, *Chemosphere* 82 (2011) 9–17.
- [148] H. Sun, F. Li, T. Zhang, X. Zhang, N. He, Q. Song, L. Zhao, L. Sun, T. Sun, Perfluorinated compounds in surface waters and WWTPs in Shenyang, China: mass flows and source analysis, *Water Res.* 45 (2011) 4483–4490.
- [149] O.S. Arvaniti, E.I. Ventouri, A.S. Stasinakis, N.S. Thomaidis, Occurrence of different classes of perfluorinated compounds in Greek wastewater treatment plants and determination of their solid-water distribution coefficients, *J. Hazard. Mater.* 239–240 (2012) 24–31.
- [150] A. Kumar, I. Xagorarakis, Pharmaceuticals, personal care products and endocrine-disrupting chemicals in U.S. surface and finished drinking waters: a proposed ranking system, *Sci. Total Environ.* 408 (2010) 5972–5989.
- [151] J.B. Ellis, Pharmaceutical and personal care products (PPCPs) in urban receiving waters, *Environ. Pollut.* 144 (2006) 184–189.
- [152] K. McLellan, R.U. Halden, Pharmaceuticals and personal care products in archived U.S. biosolids from the 2001 EPA national sewage sludge survey, *Water Res.* 44 (2010) 658–668.
- [153] M. Motoyama, S. Nakagawa, R. Tanoue, Y. Sato, K. Nomiya, R. Shinohara, Residues of pharmaceutical products in recycled organic manure produced from sewage sludge and solid waste from livestock and relationship to their fermentation level, *Chemosphere* 84 (2011) 432–438.
- [154] H. Fromme, T. Otto, K. Pilz, F. Neugebauer, Levels of synthetic musks; bromocyclene and PCBs in eel (*anguilla anguilla*) and PCBs in sediment samples from some waters of Berlin/Germany, *Chemosphere* 39 (1999) 1723–1735.
- [155] C. Miège, J.M. Choubert, L. Ribeiro, M. Eusèbe, M. Coquery, Removal efficiency of pharmaceuticals and personal care products with varying wastewater treatment processes and operating conditions – conception of a database and first results, *Water Sci. Technol.* 57 (2008), 49–.
- [156] M. Gros, M. Petrović, A. Ginebreda, D. Barceló, Removal of pharmaceuticals during wastewater treatment and environmental risk assessment using hazard indexes, *Environ. Int.* 36 (2010) 15–26.
- [157] B. Kasprzyk-Hordern, R.M. Dinsdale, A.J. Guwy, The removal of pharmaceuticals, personal care products, endocrine disruptors and illicit drugs during wastewater treatment and its impact on the quality of receiving waters, *Water Res.* 43 (2009) 363–380.
- [158] J.L. Zhou, Z.L. Zhang, E. Banks, D. Grover, J.Q. Jiang, Pharmaceutical residues in wastewater treatment works effluents and their impact on receiving river water, *J. Hazard. Mater.* 166 (2009) 655–661.
- [159] J.L. Santos, I. Aparicio, M. Callejón, E. Alonso, Occurrence of pharmaceutically active compounds during 1-year period in wastewaters from four wastewater treatment plants in Seville (Spain), *J. Hazard. Mater.* 164 (2009) 1509–1516.
- [160] A. Daneshvar, J. Svanfelt, L. Kronberg, M. Prévost, G.A. Weyhenmeyer, Seasonal variations in the occurrence and fate of basic and neutral pharmaceuticals in a Swedish river-lake system, *Chemosphere* 80 (2010) 301–309.
- [161] M.J. Martínez Bueno, M.J. Gomez, S. Herrera, M.D. Hernando, A. Agüera, A.R. Fernández-Alba, Occurrence and persistence of organic emerging contaminants and priority pollutants in five sewage treatment plants of Spain: two years pilot survey monitoring, *Environ. Pollut.* 164 (2012) 267–273.
- [162] K. Bester, Retention characteristics and balance assessment for two polycyclic musk fragrances (HCHB and AHTN) in a typical German sewage treatment plant, *Chemosphere* 57 (2004) 863–870.
- [163] S.L. Simonich, T.W. Federle, W.S. Eckhoff, A. Rottiers, S. Webb, D. Sabaliunas, W. de Wolf, Removal of fragrance materials during U.S. and European wastewater treatment, *Environ. Sci. Technol.* 36 (2002) 2839–2847.
- [164] H.P.H. Arp, C. Niederer, K.-U. Goss, Predicting the partitioning behavior of various highly fluorinated compounds, *Environ. Sci. Technol.* 40 (2006) 7298–7304.
- [165] B.C. Kelly, M.G. Ikonou, J.D. Blair, B. Surridge, D. Hoover, R. Grace, F.A.P.C. Gobas, Perfluoroalkyl contaminants in an Arctic marine food web: trophic magnification and wildlife exposure, *Environ. Sci. Technol.* 43 (2009) 4037–4043.
- [166] D.A. Ellis, T.M. Cahill, S.A. Mabury, I.T. Cousins, D. Mackay, Partitioning of organofluorine compounds in the environment, in: A.H. Neilson (Ed.), *Handbook of Environmental Chemistry*, Springer, Berlin, Germany, 2002, pp. 63–83.
- [167] K. Prevedouros, I.T. Cousins, R.C. Buck, S.H. Korzeniowski, Sources, fate and transport of perfluorocarboxylates, *Environ. Sci. Technol.* 40 (2006) 32–44.
- [168] D.C. Burns, D.A. Ellis, H. Li, C.J. McMurdo, E. Webster, An experimental pK_a determination for perfluorooctanoic acid (PFOA) and the potential impact of pK_a concentration dependence on laboratory-measured partitioning phenomena and environmental modelling, *Environ. Sci. Technol.* 42 (2008) 9283–9288.
- [169] K.-U. Goss, The pK_a values of PFOA and other highly fluorinated carboxylic acids, *Environ. Sci. Technol.* 42 (2008) 456–458.
- [170] USEPA, Long-Chain Perfluorinated Chemicals (PFCs), Action Plan (2009) <http://www.epa.gov/oppt/existingchemicals/pubs/pfcs.action.plan.1230.09.pdf>.
- [171] M.J.M. Wells, Log Dow Key to understanding and regulating wastewater-derived contaminants, *Environ. Chem.* 3 (2006) 439–449.
- [172] M.J.M. Wells, Examination of the Mobility Scoring Hierarchy Used to Select Chemicals for the U.S. EPA Contaminant Candidate List Classification Procedure [CD-ROM pp. 86–98], Proceedings of the Water Environment Federation 2007 Specialty Conference Series, Compounds of Emerging Concern: What Is on the Horizon? Providence, RI (2007).